



COMPUTATIONAL MODELING AND SIMULATION TECHNIQUES FOR MANAGING RAIL-URBAN INTERFACE CONSTRAINTS IN METROPOLITAN TRANSPORTATION SYSTEMS

Masud Rana¹; Hammad Sadiq²;

- [1]. Department of Industrial Engineering, Lamar University, USA;
BSc in Civil Engineering, Stamford University Bangladesh, Dhaka, Bangladesh;
Email: masudranasub97@gmail.com
- [2]. Senior Project Engineer, JMA Civil Inc. Oakland, California, USA;
Email: hammad.sadiq156@gmail.com

Doi: [10.63125/pxet1d94](https://doi.org/10.63125/pxet1d94)

Received: 21 September 2024; Revised: 25 October 2024; Accepted: 27 November 2024; Published: 27 December 2024.

Abstract

Rail–urban interface constraints in metropolitan transportation systems reduce reliability and safety because dense stations, corridor conflict points, and community exposure can turn small disruptions into network-wide delays and crowding. This study examined whether computational modeling and simulation capability (CMSC) improves constraint-management effectiveness (CME) in an enterprise-scale metro rail case where cloud and enterprise analytics support scenario testing and decisions. Using a quantitative, cross-sectional, case-based design, a 5-point Likert survey was administered to $N = 312$ professionals from operations/control (26.3%), planning/timetabling (20.5%), station management (17.9%), engineering/maintenance (19.9%), and safety/risk (15.4%); 41.0% were direct model users and 37.8% indirect users. Key variables were rail–urban interface constraint severity (RICS), CMSC, decision integration (DI), and CME. Data screening showed mean missingness of 1.8% and Harman single-factor variance of 32.6%. Reliability was strong (α : RICS .88, CMSC .91, DI .87, CME .90). The most severe constraints were station crowding/circulation ($M = 4.21$, $SD = 0.62$) and peak dwell-time variability ($M = 4.08$, $SD = 0.67$). CMSC was moderate-high ($M = 3.78$, $SD = 0.64$), with scenario analysis strongest ($M = 3.92$) and validation weakest ($M = 3.49$). CMSC and DI correlated positively with CME ($r = .62$ and $.58$; $p < .001$), while RICS correlated negatively ($r = -.41$; $p < .001$). Regression was significant ($R^2 = .51$): CMSC ($\beta = .38$) and DI ($\beta = .29$) increased CME, and RICS reduced it ($\beta = -.17$); CMSC benefits were stronger at higher DI ($\Delta R^2 = .03$). Implications emphasize station-area actions, stronger validation governance, and institutionalized use of simulation outputs in routine decisions.


KEYWORDS

Rail–Urban Interface; Computational Modeling and Simulation; Decision Integration; Station Crowding; Metropolitan Rail Performance.

INTRODUCTION

Rail–urban interface constraints refer to the interacting physical, operational, environmental, and safety frictions that arise where rail infrastructure and rail operations meet dense metropolitan land uses, multimodal streets, and human activity systems. In metropolitan transportation systems, this “interface” is not limited to a rail right-of-way boundary; it includes station areas as activity hubs, track-adjacent communities exposed to noise and vibration, rail-road conflict points such as crossings and junctions, and timetable-driven capacity pressures that propagate delays into citywide mobility networks (Abril et al., 2008).

Figure 1: Multi-Dimensional Rail–Urban Interface Constraints



Computational modeling and simulation techniques in this domain are the formal, algorithmic representations of rail operations and surrounding urban conditions that allow researchers to test how infrastructure, schedules, demand, and constraints co-produce measurable system outcomes. In practice, these techniques range from discrete-event representations of train movements and control logic to stochastic timetable stability analysis, optimization-supported rescheduling, and station-area pedestrian or dwell-time representations that capture passenger interaction effects (Corman et al., 2010). Globally, the significance of rail–urban interface constraints is amplified by the concentration of population, employment, and services in metropolitan corridors, where rail often functions as a backbone for high-capacity mobility and as a spatial organizer around station areas (Dröes & Rietveld, 2015). Rail-based networks also interact with land development patterns through accessibility and station-area design, making interface constraints simultaneously an engineering matter and an urban systems matter (Ewing & Cervero, 2010). Environmental constraints at the interface, including train-induced vibration transmission into buildings and rail noise perception in adjacent communities, further widen the definition from operational performance to quality-of-life exposure and infrastructure externalities (Yang et al., 2019). As a result, rail–urban interface constraints are increasingly treated as multi-dimensional phenomena where measurable performance indicators—punctuality, capacity utilization, dwell time stability, safety risk, and exposure intensity—must be studied together, rather than in isolated silos (Dewilde et al., 2014).

Metropolitan rail systems operate as tightly coupled networks in which small perturbations can spread through shared track segments, station bottlenecks, junction conflicts, and headway control regimes.

Capacity in this setting is not only a property of infrastructure, but also a function of timetable structure, signaling constraints, dwell times, and operational control rules that shape how close trains can run without destabilizing reliability (Tavakol & Dennick, 2011). Railway capacity assessment research has shown that performance degradation emerges when network utilization approaches saturation, because buffer time and operational slack become insufficient to absorb disturbances, which raises the probability of knock-on delays and reduces effective throughput (Gao et al., 2014). Timetable stability analysis formalizes this phenomenon by modeling scheduled rail operations as discrete-event dynamic systems and evaluating sensitivity to disturbances using stability criteria grounded in max-plus system theory, which helps identify critical services and structural fragilities in dense networks (Goverde, 2007). At station areas, the constraint landscape intensifies: conflicting routes, limited platform and throat capacity, and passenger-driven dwell variability create a local bottleneck that can dominate line performance, which is why robustness-focused studies emphasize station-area routing and timetable adjustments as a coupled problem rather than a purely dispatching problem (Lyu et al., 2016). Rescheduling research similarly frames disruptions as optimization-and-control challenges where centralized or distributed decision architectures impose different tradeoffs in feasibility, response speed, and global consistency under disturbance (Baker, 2012; Mohiul, 2020). In urban contexts, headway regulation becomes a core operational mechanism to stabilize service regularity, because passenger arrival processes, station congestion, and dwell time variation impose stochastic disturbances that can alter train spacing and cascade into crowding and schedule deviation (Hair et al., 2011; Jinnat & Kamrul, 2021). These operational realities connect directly to the metropolitan rail-urban interface because the external urban environment influences internal rail dynamics: station-area pedestrian circulation affects dwell processes; surrounding land use influences peak demand intensity and arrival patterns; and network accessibility influences station choice behavior, reinforcing spatial concentration at certain nodes (Ahmadi et al., 2022; Rabiul & Samia, 2021). The background literature therefore motivates a systems perspective: rail performance metrics observed at the network level frequently originate from interface constraints observable at station areas and other rail-urban contact zones, which can be represented quantitatively through computational models and validated empirically through case-based measurement.

The rail-urban interface is simultaneously a mobility interface and a spatial-development interface because station areas are where transport supply and land use demand meet and mutually condition each other. Station-area evaluation frameworks operationalize this coupling by quantifying node-like transport attributes (connectivity, service intensity, accessibility) alongside place-like urban attributes (density, diversity of activities, walkability structure), allowing classification of station contexts and identification of stress conditions where competition for space and functional conflicts intensify (Vale, 2015). Transit-oriented development (TOD) research positions stations as strategic urban anchors and uses typologies to describe how metropolitan rail nodes differ in built form, functional mix, and pedestrian conditions, which is central to understanding why interface constraints vary across locations even on the same line (Mohiul & Rahman, 2021; Tortainchai et al., 2021). Empirical TOD typology work in large metro systems illustrates that station areas can be grouped into distinct categories with different risk profiles for congestion, access friction, and development pressure, which is relevant when selecting case-study sites and interpreting constraint mechanisms (Norman, 2010; Rahman & Abdul, 2021). Built environment meta-analysis further supports the importance of measurable “D” variables—such as density, design, and destination accessibility—in shaping travel behavior around stations, which in turn shapes the temporal and spatial distribution of passenger flows into rail systems (Yuan & Hansen, 2007). This coupling makes rail-urban interface constraints multi-layered: a station’s urban form and pedestrian network affects how quickly passengers access platforms, how boarding/alighting interactions unfold, and how dwell time variability is generated at peak loads; those dwell dynamics then feed back into headway stability and capacity utilization (Zou et al., 2020). In this sense, urban spatial structure is not merely a background condition; it can be modeled as a co-determinant of operational constraints, as rail network design choices interact with congestion and urban form outcomes across metropolitan corridors (Dewilde et al., 2014; Haider & Shahrin, 2021). Computational modeling becomes necessary here because the interactions are not linear in real settings: the same timetable buffer may produce different punctuality outcomes depending on station-area

demand surges, pedestrian layout constraints, or localized route conflicts at junctions (Vale, 2015). Therefore, a rail-urban interface framing expands the research object from “rail operations” alone to “rail operations embedded in metropolitan spatial systems,” establishing why a modeling-and-simulation approach is appropriate for quantifying constraints and testing hypothesized relationships in a case-study setting.

Environmental externalities such as ground-borne vibration and radiated noise are core rail-urban interface constraints because they convert rail operations into measurable exposures within the urban fabric, especially where buildings and sensitive land uses sit close to tunnels, elevated sections, or surface tracks. Train-induced vibration propagation research demonstrates that vibration levels at receivers depend on coupled factors spanning train characteristics, track-tunnel-soil transmission paths, and the structural dynamics of buildings, which makes prediction and mitigation inherently a modeling problem rather than a purely observational problem (Gao et al., 2014). In metropolitan systems, these exposures are not uniform; they vary by infrastructure type and local geology, and they can also vary by operational regimes such as speed profiles and frequency patterns, which links environmental constraints back to timetable and control decisions (Corman et al., 2010). Studies that integrate vibration and noise considerations into metropolitan contexts show that building vibration and radiated noise can be perceived as significant adjacent impacts, positioning “service quality” as not only travel time and punctuality, but also the experienced acoustic-vibration environment for nearby residents and users (Vale, 2015; Zulqarnain & Subrato, 2021). Related assessments highlight that rail-induced vibration and noise can be discussed within sustainability-oriented performance measurement because mitigation decisions often involve tradeoffs between operational intensity, infrastructure interventions, and environmental comfort thresholds (Ahmadi et al., 2022). These environmental constraints connect to the rail-urban interface through land use decisions around rail corridors and station areas: dense development increases the number of exposed receivers, and station-area intensification can heighten sensitivity to vibration/noise because of mixed-use concentration and pedestrian-oriented environments (Uddin et al., 2022; Lyu et al., 2016). From a computational modeling perspective, including vibration/noise in an interface study supports a more comprehensive definition of “constraint,” where constraints include not only hard operational limits (capacity, headway) but also soft urban acceptability limits that shape feasible operating envelopes. This matters in metropolitan governance contexts because rail systems are frequently required to meet performance targets while remaining compatible with adjacent urban quality-of-life expectations, which makes quantitative modeling of exposures a relevant complement to modeling of punctuality and capacity (Yang et al., 2019). A research design that treats vibration/noise as measurable interface variables also aligns with cross-sectional survey approaches, where perceptions and reported impacts can be linked statistically to modeled or observed operational conditions in the chosen case-study corridor.

Safety and controllability constraints at the rail-urban interface arise where rail movements intersect with human and vehicular activity patterns, and where operational control must manage conflicts in constrained spaces. In metropolitan station areas and junctions, routing conflicts and platform constraints create operational states that require active control and, under disruption, rescheduling strategies that maintain feasibility while limiting delay propagation (Corman et al., 2010). Comparative work on centralized versus distributed rescheduling emphasizes that the architecture of control influences how quickly feasible solutions can be generated and how well local decisions remain consistent with network-level goals, which is essential when disruptions occur near dense urban bottlenecks (Dewilde et al., 2014; Akbar & Sharmin, 2022). Station-area robustness research further shows that improving stability is not a single-variable adjustment: it often involves iterative coupling of route optimization through bottlenecks with timetable modifications, reinforcing the role of simulation and optimization as complementary methods (Dröes & Rietveld, 2015; Foysal & Subrato, 2022). In high-frequency urban rail operations, headway regulation is a safety-and-service control function because unstable headways can increase platform crowding risk, degrade boarding processes, and generate operational states that stress signaling and station throughput (Gao et al., 2014). At the passenger interface, dwell time efficiency research illustrates that station performance cannot be explained solely by infrastructure; passenger interaction effects and directional flows shape dwell outcomes and can be evaluated quantitatively using efficiency-oriented analytics when demand and

movement data are available (Corman et al., 2010; Rahman, 2022). From a quantitative research standpoint, these safety-and-control constraints provide measurable constructs that can be operationalized into survey items and tested statistically: perceived reliability, perceived crowding pressure, perceived safety and controllability, and reported disruption experience can be linked to modeled or observed indicators such as buffer time, knock-on delays, and headway variability (Tortainchai et al., 2021; Zulqarnain, 2022). This supports a computational-empirical integration where simulation outputs serve as explanatory context for cross-sectional measurement, and the case-study setting anchors variables in an identifiable metropolitan rail-urban interface environment.

Within metropolitan transportation systems, rail-urban interface constraints can be framed as a measurable gap between intended rail performance (capacity utilization with stability, controllability with safety, and compatibility with adjacent urban conditions) and observed operational and urban experience outcomes (delay propagation, dwell time instability, localized bottlenecks, and vibration/noise exposure). Capacity assessment literature provides the operational side of this framing by demonstrating that infrastructure and timetable designs impose quantifiable limits and that performance degradation accelerates as utilization rises (Dröes & Rietveld, 2015; Habibullah & Mohiul, 2023). Timetable stability analysis strengthens the framing by offering formal measures for robustness-to-disturbance, which becomes an empirical problem when contrasted with real system variability in dense networks (Goverde, 2007). Station robustness and rescheduling studies similarly show that bottleneck areas can dominate system reliability and that combined optimization-simulation approaches are appropriate for representing these constraint mechanisms (Jabed Hasan & Waladur, 2023; Tavakol & Dennick, 2011). On the urban side, TOD and station-area classification work indicates that constraints are spatially differentiated across station contexts, meaning that operational issues and user experiences may vary systematically with place characteristics, pedestrian accessibility, and surrounding land-use intensity (Baker, 2012; Corman et al., 2010). Environmental vibration/noise modeling adds an additional measurable layer where rail operation intensity and infrastructure form can correspond to exposure patterns experienced by adjacent receivers (Rabiul & Mushfequr, 2023; Shahrin & Samia, 2023; Yang et al., 2019). A quantitative, cross-sectional, case-study-based approach aligns with these constructs because it allows the research to measure stakeholder perceptions and reported experiences at a single point in time, while linking those measures to computationally derived or operationally observed indicators. The use of a five-point Likert scale is consistent with widely used measurement practices for attitudes and perceptions, and established methodological discussions support the treatment of Likert-type responses in applied statistical analysis when instrument quality and reliability checks are performed (Corman et al., 2010; Rakibul & Alam, 2023; Rifat & Rebeka, 2023). Instrument credibility in this setting depends on reliability and validity evidence, where internal consistency indicators such as Cronbach's alpha are commonly reported and interpreted as part of measurement quality assessment (Lyu et al., 2016). Construct modeling traditions in applied research further emphasize careful specification of measurement models and evidence-based evaluation of reliability and validity before interpreting correlation and regression relationships, particularly when hypotheses are tested using survey-derived indicators (Baker, 2012; Kumar, 2023; Saikat & Aditya, 2023). These methodological foundations connect directly to the study's purpose: to quantify how computationally representable constraint mechanisms at the rail-urban interface relate to measurable operational and user-experience outcomes in a defined metropolitan case setting.

A structured introduction to rail-urban interface research benefits from both a theoretical framing for how complex system innovations are adopted and governed, and a conceptual framing for how interface constraints are represented as measurable constructs (Masud & Hossain, 2024; Zulqarnain & Subrato, 2023). The Technology-Organization-Environment (TOE) framework is frequently used to explain how technological capabilities, organizational readiness, and environmental pressures shape the adoption and effective use of complex analytic systems, which fits the context where rail agencies and metropolitan stakeholders implement modeling, simulation, and decision-support practices under performance and urban compatibility pressures (Corman et al., 2010; Md & Praveen, 2024; Nahid & Bhuya, 2024). A complementary conceptual framing is offered by station-area evaluation work that combines transport supply, land use intensity, and pedestrian accessibility into integrated indices and typologies, enabling the study to define and measure "interface constraints" in a way that is

operationally meaningful and spatially explicit within the selected metropolitan case (Akbar, 2024; Md. Foyzal & Abdulla, 2024; Tavakol & Dennick, 2011). Within this combined framing, computational simulation and stability analysis can be treated as the technical layer that represents operational constraints (capacity, timetable robustness, bottleneck conflict), while survey-derived measurement captures perceived performance and experienced interface conditions that reflect organizational and environmental contexts (Abril et al., 2008; Ibne & Aditya, 2024; Mosheur & Arman, 2024). Environmental constraint modeling extends the conceptual scope by linking infrastructure and operational conditions to vibration/noise outcomes within the surrounding city, making the rail-urban interface measurable through both operational indicators and adjacent exposure indicators (Lyu et al., 2016; Rabiul & Alam, 2024; Saba & Hasan, 2024). Methodologically, the introduction establishes why descriptive statistics, correlation analysis, and regression modeling are coherent choices for a cross-sectional case study that tests hypothesized relationships among operational constraint indicators, station-area context variables, and reported system outcomes, provided that instrument reliability and construct quality evidence are documented using standard practices (Kumar, 2024; Praveen, 2024; Tavakol & Dennick, 2011). Following this introduction, the paper is organized into a literature review that synthesizes rail capacity and timetable stability, station-area robustness, station context and TOD typologies, and environmental vibration/noise evidence; a methodology section that details the case-study context, sampling, instrument design, and data quality procedures; a results section reporting profiles, screening checks, descriptive findings, reliability evidence, correlations, and regression diagnostics (Shaikat & Aditya, 2024); and subsequent discussion, conclusion, recommendations, limitations, and study boundaries aligned with the tested hypotheses and research questions.

The present study is structured around three tightly connected objectives that translate the broad challenge of rail-urban interface constraints into measurable, case-grounded components suitable for quantitative testing within a metropolitan rail context. The first objective is to identify and prioritize the most consequential rail-urban interface constraints operating in the selected case setting, treating constraints as multidimensional conditions that manifest through operational bottlenecks, station-area frictions, safety and controllability pressures, spatial and access limitations, and environmental disturbance concerns. This objective emphasizes systematic description and ranking, so that constraint intensity can be mapped across respondent groups and linked to observed patterns of service performance and interface experience within the case system. The second objective is to measure the level, structure, and perceived operational usefulness of computational modeling and simulation practices deployed for managing these constraints, focusing on how modeling is used for scenario analysis, how simulation outputs are incorporated into planning and operational decisions, how model validation and verification practices are carried out, and how usability and organizational acceptance shape routine application. This objective treat modeling and simulation as an actionable capability set rather than a purely technical artifact, allowing the study to quantify variation in practice maturity across departments and professional roles in the same metropolitan system. The third objective is to test the statistical relationships between modeling/simulation practices and rail-urban constraint-management performance outcomes, using correlation and regression modeling to evaluate the strength, direction, and explanatory power of modeling-related variables in predicting performance outcomes that represent operational efficiency, reliability, safety effectiveness, and urban compatibility at the interface. This objective is designed to establish whether differences in modeling practice quality and integration correspond to differences in reported performance outcomes across the case, while controlling for respondent characteristics where appropriate. Taken together, these objectives create a coherent pathway from problem specification to measurement and empirical testing: the study first clarifies what constraints dominate, then measures how computational modeling is applied to address them, and finally evaluates how strongly these practices are associated with performance outcomes within the selected metropolitan rail-urban interface environment.

LITERATURE REVIEW

The literature on computational modeling and simulation for managing rail-urban interface constraints spans multiple, interlocking streams that collectively explain why metropolitan rail systems experience persistent bottlenecks and why analytic tools are increasingly used to diagnose, evaluate, and manage these constraints in practice. At the operational level, research on railway capacity, timetable stability,


delay propagation, and disruption management establishes that high-frequency metropolitan rail networks behave as tightly coupled systems in which small disturbances can cascade through shared infrastructure, junction conflicts, station bottlenecks, and headway control processes, producing measurable impacts on reliability, throughput, and passenger experience. In parallel, station-focused studies emphasize that stations and their surrounding areas operate as critical interface points where passenger demand surges, platform and throat limitations, multimodal access congestion, and boarding–alighting interactions create dwell-time variability and localized capacity constraints that can dominate corridor performance. A second major stream connects rail operations with urban spatial structure by framing station areas as the primary locations where transport supply meets land-use demand; this work highlights how built-environment intensity, accessibility, and pedestrian network design shape passenger flows and station-area pressure, thereby influencing operational conditions at the interface. A third stream addresses environmental and social acceptability constraints, particularly rail-induced noise and vibration, which extend the concept of “constraint” beyond operational limits into the domain of urban compatibility, community exposure, and mitigation tradeoffs that can restrict feasible operating regimes in dense metropolitan settings. Alongside these domain streams, methodological studies contribute approaches for representing rail–urban interface phenomena using simulation, optimization, and hybrid analytics, including discrete-event modeling of train movements, agent-based representations of interactions, microsimulation around station access and crossings, stochastic models for demand and dwell processes, and integrated decision-support approaches for scenario testing. Finally, adoption- and governance-oriented scholarship explains that the effectiveness of modeling and simulation depends not only on technical sophistication but also on organizational readiness, data availability, validation culture, and the extent to which analytic outputs are integrated into planning and operational decisions across stakeholders. Synthesizing these strands provides the foundation for the present study’s literature review: it clarifies how rail–urban interface constraints are defined and measured, how modeling and simulation techniques have been applied to evaluate these constraints, what performance outcomes are commonly associated with improved constraint management, and why empirical, case-based quantitative testing is necessary to connect modeling practices to observed operational and urban-interface outcomes in metropolitan transportation systems.

Rail–Urban Interface in Metropolitan Transportation Systems

Rail–urban interface in metropolitan transportation systems refers to the functional boundary zone where rail infrastructure and services intersect with the city’s land uses, public realm, and multimodal circulation patterns, producing interactions that shape both rail performance and urban experience. In practical terms, the interface includes stations as major access gateways, track-adjacent neighborhoods, interchanges, and corridor segments where rail operations coexist with dense human activity, complex street networks, and competing claims for space. This interface is best understood as a coupled system rather than a single location because constraints often emerge through combined effects of network connectivity, station-area intensity, and the spatial organization of daily activities around rail nodes. A foundational view conceptualizes stations as simultaneously “nodes” in transport networks and “places” in the urban fabric, meaning they must serve high-capacity movement while also accommodating diverse urban functions and social uses. When node and place roles are misaligned – such as high connectivity without sufficient urban capacity to absorb flows, or high urban intensity without adequate transport support – stress accumulates as congestion, access friction, and operational instability at the interface. Empirical classification work has demonstrated how this balance can be measured and used to interpret station-area variability within national or metropolitan rail systems, providing structured ways to distinguish station contexts and anticipate which types are prone to particular interface pressures (Reusser et al., 2008). At a finer level, longitudinal and spatial development analyses of station areas show that rail–urban interface conditions are dynamic, shaped by redevelopment cycles, accessibility shifts, and institutional strategies that reconfigure how station precincts function over time. Such work strengthens the definition of the rail–urban interface by positioning it as an evolving socio-technical environment where transport supply, land development, and governance decisions continuously reshape constraint patterns and performance outcomes (Chorus & Bertolini, 2011).

A metropolitan perspective emphasizes that rail–urban interface constraints are not only operational but also spatial and relational, because stations organize mobility at multiple scales: local walking access, feeder modes, and regional rail connectivity. In dense metropolitan regions, the interface becomes a primary arena where rail accessibility influences urban form, and urban form in turn modifies rail demand, station usage intensity, and access conditions. The interface can therefore be framed through accessibility as a measurable linkage between rail service structures and the distribution of opportunities in the city, capturing how station areas function as gateways to employment, services, and social activities. Comparative metropolitan research has shown that transit-oriented development characteristics and rail-based accessibility are related in systematic ways across different European regions, reinforcing the idea that the rail–urban interface is simultaneously a transport phenomenon and an urban-structure phenomenon. This view is important because constraints at the interface may arise when the spatial pattern of development concentrates demand beyond what station access networks, platform circulation, or interchange layouts can comfortably handle. In this framing, interface constraints include the operational outcomes that riders feel—crowding, delays, irregularity—as well as the physical conditions of access, such as walkability, feeder integration, and station-area permeability. Cross-metropolitan analysis further supports treating station areas as comparative units for understanding interface performance, because accessibility profiles and development patterns vary by urban structure and network design, producing different risk profiles for station overload and corridor stress (Papa & Bertolini, 2015). Empirical modeling approaches extend this by operationalizing station accessibility using indicators that represent both transport supply and land-use context, offering practical tools for diagnosing where interface frictions are likely to occur and for prioritizing interventions. Large-scale station assessment applications show how a structured accessibility instrument can classify stations and reveal comparative advantages or deficits that matter for planning and operational coordination at the metropolitan scale (Caset et al., 2018).

Figure 2: Rail–Urban Interface Framework Integrating Node–Place Balance



The rail–urban interface also includes environmental and infrastructure interaction constraints that become more pronounced in metropolitan settings where rail lines and stations are embedded in close proximity to buildings, sensitive land uses, and public spaces. In these contexts, rail operations generate measurable externalities such as ground-borne vibration and structure-borne noise, and these effects can become binding constraints on rail operations, infrastructure upgrades, and surrounding development acceptability. Unlike purely internal operational constraints, environmental interface constraints operate through exposure pathways that depend on vehicle–track dynamics, local infrastructure conditions, and receiver characteristics, making them complex and site-specific. This reinforces the need to treat the rail–urban interface as a multi-domain constraint environment, where system performance is evaluated not only through reliability and throughput but also through compatibility with the surrounding city. The international relevance of these constraints is amplified by the growth of urban rail, light rail, and metro networks in dense cities, where even small changes in service frequency, speed, or track condition can alter exposure patterns and public tolerance. As a result, interface management is not only about moving trains efficiently; it is also about maintaining acceptable interactions with adjacent urban systems and ensuring that rail remains a socially and environmentally compatible backbone of metropolitan mobility. Review-level evidence has documented the increasing prominence of railway ground vibration as an urban problem and synthesized how such impacts are assessed and managed, reinforcing the idea that rail–urban interface constraints include a technical–environmental dimension that must be incorporated into metropolitan rail planning and evaluation (Connolly et al., 2016). In this study’s framing, the rail–urban interface therefore functions as an integrated constraint arena—linking station-area spatial structure, accessibility and node-place balance, multimodal access conditions, and environmental compatibility—within which computational modeling and simulation can support systematic diagnosis and performance-oriented management.


Key Rail–Urban Interface Constraints in Metropolitan Systems

Rail–urban interface constraints in metropolitan corridors often emerge first as station-area capacity and circulation limits that shape how reliably trains can interact with dense urban passenger flows. In this context, constraints are not only “hard” infrastructure limits (e.g., platform width, escalator capacity, concourse geometry), but also operational coupling between passenger arrival surges, door-level boarding/alighting friction, and the dwell time required to complete exchanges safely. When station access points funnel large volumes into narrow channels, small disturbances (a late train, uneven door demand, a platform bottleneck) can propagate into longer dwell times and wider headway variability, reducing effective line capacity even when nominal train frequency is unchanged. Modeling work on metro dwell times emphasizes that robust planning requires treating dwell time as flow-dependent rather than fixed, because passenger volumes and their spatial distribution across doors strongly influence the stop duration and the likelihood of cascading delay amplification in dense operations (D’Acerno et al., 2017). Complementing the dwell-time perspective, empirical congestion evaluation in metro stations shows that bottlenecks differ by facility type (channels, stairways, platforms) and that congestion can reach severe levels on platforms under high-density conditions, requiring targeted operational control (e.g., gating, directional management, timed holding) and design interventions (e.g., widening, rebalancing circulation, improving vertical distribution) to prevent safety and service degradation (Zhou et al., 2019). Together, these studies position station micro-constraints as measurable, modelable interface phenomena in which infrastructure and passenger behavior jointly determine whether metropolitan rail can absorb urban demand peaks without compromising reliability.

A second major category of rail–urban interface constraints arises from the physical embedding of rail corridors into the city fabric, where rail lines can function simultaneously as mobility connectors and as barriers to local movement. In dense urban contexts, at-grade and grade-separated crossings, fencing, and corridor design can produce community severance, lengthening pedestrian and cyclist routes and concentrating crossing demand into a small number of nodes that become both mobility chokepoints and perceived-safety hotspots. Quantitative barrier-effect work highlights that railways and other major infrastructures can impose strong local accessibility penalties even while delivering regional accessibility gains, implying that interface performance must be evaluated across multiple

spatial scales and user groups rather than inferred from network-level travel time benefits alone (van Eldijk, 2019). Closely related are road–rail conflict constraints where rail operations intersect with urban street systems at level crossings, creating a compound interface problem: exposure to collision risk, delay to road users, and operational vulnerability for rail. Risk modeling using causal/Bayesian approaches demonstrates how level crossing safety is driven by interacting factors (infrastructure, protection systems, operational context, and human behavior), reinforcing that interface constraints can be represented probabilistically and linked to prioritized mitigation (e.g., protection upgrades, warning design, behavior-focused countermeasures) (Liang et al., 2017). In metropolitan rail–urban systems, these corridor constraints often surface as recurring points of delay, safety concern, and political contestation because they sit at the intersection of rail performance, street network function, and neighborhood permeability.

Figure 3: Key Rail–Urban Interface Constraints in Metropolitan Systems



A third constraint set is environmental and perceptual, centered on noise exposure and annoyance in dense urban settings where rail pass-bys are frequent, temporally patterned, and often audible indoors. Environmental constraints matter at the rail–urban interface because they shape the acceptability of service intensity, infrastructure expansion, and corridor operations (especially freight or late-night services), and they can trigger design requirements that interact with operational goals (e.g., speed management, track form, barriers, façade treatments). Evidence from controlled or quasi-experimental work comparing indicators of magnitude, spectrum, and temporal evolution indicates that annoyance responses are not captured by a single overall noise level alone; rather, temporal and spectral descriptors can improve explanatory models of perceived annoyance for both road and rail sources, especially when exposure is defined as realistic indoor sound (Torija et al., 2011). For metropolitan rail planning, the implication is that the interface “constraint” is partly a socially experienced threshold: rail may be operationally feasible, yet environmentally contested when the acoustic signature or timing of operations crosses perceived tolerances in adjacent neighborhoods. This also means that rail–urban interface modeling benefits from integrating environmental variables (exposure metrics, indoor audibility, event timing) with operational variables (frequency, speed profiles, stopping patterns), because the same service plan can yield different levels of acceptability depending on corridor morphology and building contexts. In practical terms, environmental constraints become tightly coupled to urban design choices around corridor buffering, station-area redevelopment, and alignment decisions, making them an essential part of a metropolitan “constraint portfolio” rather than an external afterthought.

Techniques for Managing Rail-Urban Interface Constraints


Computational modeling and simulation provide a structured way to represent how rail operations interact with dense metropolitan conditions, allowing rail-urban interface constraints to be expressed as measurable mechanisms rather than treated as isolated symptoms. A common starting point is discrete-event simulation (DES), which models rail systems as sequences of events—train arrivals, departures, signal clearances, passenger boarding completions, and conflict resolutions—so that capacity, reliability, and delay propagation can be examined under realistic operating rules. DES is particularly valuable at the rail-urban interface because urban constraints are often triggered by timing mismatches and bottlenecks: short headways, high passenger accumulation, platform and throat limitations, and route conflicts near junctions. When these constraints are encoded into a DES model, analysts can test how changes in service frequency, dwell assumptions, or control rules alter system outcomes such as average passenger waiting time, headway regularity, and platform crowding risk. A second layer frequently added to DES is simulation-based optimization, which uses repeated simulation runs to search for better operating policies, especially for timetable and headway decisions that must balance service quality with capacity and feasibility under uncertainty. In metropolitan settings, uncertainties such as fluctuating demand, variable dwell time, and travel time variation are central to interface performance, meaning the modeling approach must treat variability as a key driver, not as noise. A strong example is the application of a two-stage simulation-based optimization framework to urban rail transit planning, where simulation is used to evaluate performance while an optimization procedure searches for service plans that reduce expected passenger waiting and improve robustness under operational uncertainty ([Hassannayebi et al., 2014](#)).

Beyond network-wide performance, rail-urban interface constraints often concentrate in station areas, where passenger circulation and facility design shape dwell times, safety margins, and the practicality of service intensity. In these contexts, modeling shifts toward pedestrian and passenger-flow simulation, including microscopic representations that capture interactions among pedestrians, access gates, stairs/escalators, corridors, platforms, and vehicle doors. The strength of this family of models is its ability to show how spatial bottlenecks and directional conflicts emerge at particular points, how congestion evolves over time, and how operational measures (holding, gating, queue channelization, directional assignments) can redistribute pressure. For metropolitan operators, credibility depends on whether a simulation tool can reproduce relevant causality—how demand surges create congestion, how congestion affects walking speed and queue formation, and how these conditions feed back into boarding, alighting, and dwell-time variability. Because multiple commercial and research simulators exist, the literature also includes evaluation work that treats simulation as an operational decision-support resource and tests whether tools align with traffic-management needs, calibration requirements, and organizational constraints around deployment. This “model assessment” perspective is important for rail-urban interface studies because it clarifies that selecting a simulator is not only a technical choice; it determines what causal pathways can be represented, what data are needed, and how outputs can be translated into implementable station strategies. A focused example is an assessment of pedestrian simulation tools for railway-station traffic management that emphasizes both scientific representativeness and practical usability for managing crowd flows in complex station environments ([Dubroca-Voisin et al., 2019](#)).

A third modeling direction addresses interface constraints that arise under disruptions and emergencies, where metropolitan rail systems face sudden reductions in capacity and heightened safety requirements while continuing to interact with the surrounding city. In these cases, simulation must capture not only “normal” operations but also degraded modes, abnormal control logic, and time-critical decisions. Multi-agent approaches are increasingly used because they allow trains, control elements, and sometimes passengers to be represented as interacting decision entities, which is useful when the system response depends on localized conditions and decentralized actions. Emergency-oriented modeling also highlights the need for computational efficiency, because operators require timely evaluation of scenario impacts and feasible response policies. A representative study proposes a discrete-event simulation method built on a multi-agent model with parallel computing to estimate metro train operations under emergency conditions, illustrating how detailed motion and control representation can be combined with scalable computation to evaluate performance consequences

quickly (Li et al., 2021).

Figure 4: Computational Simulation Approaches for Analyzing Rail–Urban Interface Constraints




In parallel, simulation research in metropolitan rail emphasizes hybrid approaches, where simulation is used for realism and validation, while optimization provides structured search and policy improvement. The contribution of this hybrid tradition is to move from describing congestion and instability to prescribing actionable interventions—optimized headways, revised timetables, rescheduling heuristics, and station-control strategies—while maintaining feasibility under urban constraints. Classic metro-line work combining discrete-event simulation with response-surface methodology demonstrates how simulation outputs can be transformed into a tractable optimization surface to tune headways against passenger travel-time objectives (Yalçınkaya & Bayhan, 2009). Finally, integrative scholarship consolidates these developments by framing simulation and optimization as complementary pillars for railway operations management across strategic, tactical, and operational decisions, including multimodal considerations that are central in metropolitan rail–urban interfaces (D’Ariano et al., 2018).

Theoretical Framework for Modeling-and-Simulation

A suitable theoretical foundation for explaining how computational modeling and simulation (CMS) improve management of rail–urban interface constraints is an integrated TOE–Diffusion–Capabilities lens. At the organizational level, the Technology–Organization–Environment (TOE) framework clarifies why some metropolitan rail organizations adopt and institutionalize complex digital decision tools while others do not, even when they face similar urban constraints. TOE treats adoption as a function of (i) technology context (e.g., data quality, interoperability, perceived advantage and complexity), (ii) organizational context (e.g., managerial support, skills, governance routines, budget capacity), and (iii) environmental context (e.g., regulatory pressures, vendor ecosystems, inter-agency coordination, stakeholder scrutiny). Empirical TOE applications demonstrate that adoption and governance are not explained by technical merit alone; organizational and governance conditions can amplify or suppress the conversion of “available technology” into “implemented capability” (Borgman et al., 2013). In rail–urban settings, this is essential because CMS requires sustained integration across timetable planning, operations control, passenger management, and asset maintenance—functions that often sit in separate units with different incentives. TOE also aligns with how rail agencies experience external constraints (e.g., noise rules, safety oversight, public accountability) because these pressures

shape which scenarios are considered legitimate and which performance indicators dominate decision-making. Cross-industry evidence further supports TOE's utility for explaining why adoption drivers vary by sector and competitive structure—an important point for rail agencies operating in different metropolitan governance environments and service models (Oliveira & Martins, 2010).

Figure 5: Integrated TOE-Diffusion-Capabilities Framework for Rail-Urban Constraint Management



To complement TOE's "why adoption happens" logic, Diffusion and assimilation theory explains "how adoption deepens into routine use," which is particularly relevant for CMS because value is realized only after tools become embedded in planning and control cycles. Diffusion research conceptualizes technology uptake as a staged process (e.g., initiation → adoption → routinization), where early evaluation differs from post-adoption integration, and where contextual factors may exert different effects across stages. This staged perspective helps explain common rail analytics problems: pilots that succeed technically but fail to routinize, models that are built but not used in operational decisions, and simulations that inform one-off studies without becoming part of governance. A diffusion-based assimilation model also fits the rail-urban interface because constraints are multi-domain and persistent; routinization requires repeated scenario testing, continuous recalibration, and institutional learning as land use and demand evolve. Evidence from international diffusion modeling shows that organizational and environmental conditions shape not only adoption but also later-stage assimilation and routinization—precisely the stages where CMS becomes credible enough to influence service plans, disruption responses, and station interventions (Zhu et al., 2006). In practice, this implies that the study's theoretical framework should treat CMS maturity as a multi-dimensional construct (data readiness, verification/validation routines, integration into meetings and approvals, and user competence) rather than a binary "has software / does not have software" indicator. This framing directly supports a cross-sectional survey approach because respondents can rate observable routinization signals (frequency of scenario use, decision reliance, and cross-unit sharing of outputs), allowing quantitative testing of how assimilation maturity relates to perceived constraint-management outcomes.

Finally, to connect CMS adoption/assimilation to measurable performance outcomes, the framework should incorporate the resource-based view (RBV) and dynamic capabilities logic: CMS is valuable when it becomes a capability that enables sensing, learning, and reconfiguration under uncertainty—conditions that typify metropolitan rail-urban interfaces (Wang & Ahmed, 2007). CMS can be theorized

as an analytics capability bundle that transforms data and models into actionable insight (e.g., identifying binding bottlenecks, testing headway policies, evaluating station crowd controls) and then into operational/strategic adjustments. Empirical IS research shows that analytics capabilities often influence performance indirectly by strengthening dynamic capabilities and operational capabilities rather than producing simple direct effects (Mikalef et al., 2020). For this study, that logic can be operationalized with a regression-based model consistent with the quantitative design. Let Y denote rail-urban constraint-management performance (a composite score reflecting reliability at interface points, station flow stability, and perceived compatibility), and let CMS capability maturity be CMS , with TOE-context factors T , O , and E (technology, organization, environment), plus controls Z (role, experience, department, exposure intensity). The core specification can be stated as:

$$Y_i = \beta_0 + \beta_1 CMS_i + \beta_2 T_i + \beta_3 O_i + \beta_4 E_i + \beta_5 (CMS_i \times O_i) + \gamma' Z_i + \varepsilon_i$$

This equation reflects the theoretical claim that CMS capability matters (β_1), but its effectiveness is conditioned by organizational readiness (β_5), consistent with TOE governance arguments and dynamic capability logic. In addition, assimilation can be tested as a mediator or staged proxy using an additional construct (e.g., $ASIM$) derived from diffusion theory, enabling alternative models such as $CMS \rightarrow ASIM \rightarrow Y$ without changing the cross-sectional structure. The combined TOE-Diffusion-Capabilities framework therefore gives the study a coherent explanation chain: contextual conditions drive CMS adoption and governance, diffusion processes explain routinization, and capabilities logic explains why routinized CMS improves constraint-management performance in metropolitan rail-urban systems.

Modeling/Simulation and Rail-Urban Outcomes

A conceptual framework for this study operationalizes the rail-urban interface as a constraint-capability-outcome system in which measurable constraints (independent conditions) interact with computational modeling and simulation capability (organizational/technical capacity) to influence metropolitan rail performance outcomes (dependent results). In this framework, Rail-Urban Interface Constraint Severity (RICS) is treated as a multidimensional construct capturing station-interface frictions (crowding, dwell variability, access bottlenecks), corridor-interface frictions (conflict points, barrier effects, disturbance sensitivity), and service-interface frictions (irregular headways, delay spillovers). Computational Modeling & Simulation Capability (CMSC) represents the extent to which an agency can build, validate, and apply models for diagnosing constraints and evaluating interventions. The conversion of CMSC into performance benefits is theorized to depend on Decision Integration (DI)—how frequently model outputs are used in planning meetings, timetable revisions, control-room decisions, and station-management protocols. The outcome side includes Constraint-Management Effectiveness (CME) expressed through reliability, passenger flow stability, perceived safety in station areas, and service quality. A practical way to express CME in analytic terms is to define a composite index that aggregates standardized indicators, for example:


$$CME = \sum_{k=1}^K w_k Z_k, \sum_{k=1}^K w_k = 1$$

where Z_k are standardized scores for reliability, crowding stability, interface safety perception, and operational responsiveness. To anchor the “constraint” component in established rail-quality measurement logic, the framework also incorporates perceived service quality thresholds via a zone-of-tolerance idea, where a quality shortfall can be expressed as a gap between perceived performance and acceptable performance for a given attribute j :

$$Gap_j = P_j - A_j$$

and overall quality pressure can be summarized by the distribution of such gaps across attributes relevant to station and corridor interfaces (Cavana et al., 2007).

Figure 6: Conceptual Analytical Framework for Modeling-and-Simulation-Enabled Rail-Urban Constraint Management



The framework then specifies how CMSC and DI relate to the mechanisms by which constraints are managed, particularly under oversaturated metropolitan conditions where passenger accumulation and control strategies become central. Conceptually, the study treats Operational Control and Planning Strategies (OCPS) as the primary mediating pathway between CMSC and CME. OCPS includes timetable refinement, headway control, passenger flow control (e.g., gating/holding), and contingency actions that are selected and tuned using model evidence. This mediation is supported by optimization-based rail research showing that integrating timetable decisions with passenger flow control can reduce platform congestion and waiting-time burdens when demand exceeds capacity, thereby directly targeting the rail-urban interface where station areas become binding constraints (Shi et al., 2018). In the same conceptual logic, metropolitan rail performance is sensitive to small disturbances that propagate through tightly coupled networks, so CMSC is expected to improve CME by enabling better anticipation of delay cascades and more realistic evaluation of recovery actions. Stochastic delay-propagation modeling provides a clear mechanism for this linkage by showing how primary delays can generate network-wide secondary delays and how probabilistic forecasting can support real-time or near-real-time management decisions under uncertainty (Berger et al., 2011). Accordingly, the framework treats “interface performance” as something that depends on both structural conditions (crowding, connectivity, bottlenecks) and operational adaptability (how quickly and accurately the system responds to deviations), which CMSC strengthens through scenario testing, sensitivity analysis, and evidence-based protocol design.

Finally, the conceptual framework translates into testable hypotheses using a regression structure consistent with the study design and Likert-scale measurement. The central claim is that CMSC improves CME, but that the effect is stronger when DI is high and when OCPS is actively used, meaning the “tool-to-outcome” link is conditional rather than automatic. This can be represented with an interaction-based specification:

$$CME_i = \beta_0 + \beta_1 CMSC_i + \beta_2 DI_i + \beta_3 (CMSC_i \times DI_i) + \gamma' X_i + \varepsilon_i$$

where X_i includes controls such as respondent role, experience, unit affiliation, and exposure to peak-period operations. The interaction term operationalizes the conceptual point that model capability has greater practical impact when embedded in decisions. A related extension is to test whether OCPS

mediates the CMSC→CME relationship by estimating models with and without OCPS and observing coefficient changes in β_1 . The framework also connects CME to user-facing service perception, because metropolitan rail–urban interface constraints are experienced most directly by passengers in station areas and during service disruptions. Survey-based evidence from metro systems shows that perceived safety/comfort, infrastructure quality, and ticketing/service facilities cluster into meaningful factors that predict satisfaction, which aligns with the framework’s outcome construct and supports measuring CME partially through user-experience lenses (Saw et al., 2020). At the control/dispatch level, the framework anticipates that CMSC and DI improve CME by enabling faster, scalable rescheduling logic; distributed model predictive control research demonstrates how network-scale rescheduling can be made computationally feasible while reducing delays, supporting the inclusion of “responsiveness under disturbances” as an outcome dimension (Kersbergen et al., 2016).


Synthesis of Key Gaps

Across metropolitan rail–urban interface research, a consistent theme is that constraints emerge from coupled passenger–service–infrastructure dynamics, yet many studies still examine these elements in partial isolation. Operational modeling research has demonstrated that explicit capacity constraints – such as station entry limits, platform limits, and train capacity – can be embedded into network-level formulations to reduce passenger waiting and minimize stranded volumes, indicating that “constraint management” can be represented as a tractable system problem when the correct state variables are modeled (Fu et al., 2020). Likewise, analytical delay research has shown that delay propagation can be approximated in closed form and linked to timetable design decisions such as supplement time and buffer time, supporting rapid insight for planning contexts where repeated simulation runs may be costly (Harrod et al., 2019). These contributions clarify how strongly metropolitan outcomes depend on interaction between infrastructure and operational rules, but they also reveal a gap that is central to the rail–urban interface lens: technically rigorous models are frequently presented without measuring how modeling outputs are integrated into organizational decision processes, stakeholder negotiations, and operational governance routines in dense urban settings. In practice, metropolitan constraint management is not only an engineering optimization task; it is also a coordination and legitimacy task that depends on whether model outputs are trusted, interpretable, and routinely used by planners, dispatchers, station managers, and partner agencies. This gap matters because rail–urban interface zones are precisely where operational goals interact with urban safety expectations, public scrutiny, and multi-actor responsibilities, making it necessary to study modeling/simulation capability together with decision integration and perceived effectiveness in a single empirical frame. A case-based, cross-sectional design can address this by quantifying both the perceived maturity of modeling/simulation practices and the consistency with which outputs are used in decision cycles, and then relating those measures statistically to reported constraint-management outcomes within a defined metropolitan context.

A second gap appears in the behavioral and informational layer of rail–urban interface constraints, especially under crowding and uneven passenger distribution across trains and station spaces. Simulation research in public transport has shown that predictive real-time crowding information can alter how passengers distribute themselves across cars, changing load patterns and potentially reducing extreme congestion conditions under certain demand levels (Peftitsi et al., 2022). In parallel, revealed-preference evidence indicates that crowding discomfort has measurable behavioral impacts, including willingness to incur extra time costs to secure seating, supporting the idea that crowding is not just a subjective complaint but a quantifiable disutility with planning relevance (Tirachini et al., 2016). Even so, many crowding and information studies remain outcome-focused – documenting distribution effects or comfort valuation – without fully linking the chain from modeling evidence to operational control decisions and then to interface performance outcomes such as reliability, headway stability, platform crowd risk, and perceived station safety. For rail–urban interface management, the missing element is often an integrated evaluation that connects passenger-side mechanisms (crowding perception, distribution response, access friction) with decision-side mechanisms (headway control, gating, dwell-time interventions, platform management) using measurable constructs that represent “constraint management” rather than only “passenger comfort.” Quantitatively, this can be expressed by defining an interface-performance indicator as a combined function of operational regularity and

crowding stability, where headway irregularity and congestion pressure jointly represent the severity of interface breakdown. Many prior works measure pieces of this combined mechanism separately; in contrast, a survey-based quantitative study can measure perceived decision integration of modeling/simulation outputs and test its statistical association with composite constraint-management outcomes, strengthening empirical understanding of how modeling translates into improvements at the rail–urban boundary.

Figure 7: Key Gaps in Rail–Urban Interface Research




A third gap concerns measurement integration and hypothesis testing: several studies offer robust modeling or service-quality frameworks, yet fewer provide survey-compatible constructs that enable cross-sectional testing of how modeling/simulation capability relates specifically to rail–urban interface constraints. Passenger satisfaction modeling for urban rail has successfully used latent-construct approaches to quantify perceptions of service attributes and connect them to satisfaction outcomes, demonstrating that structured measurement is feasible in rail contexts (Shen et al., 2016). However, service satisfaction is often measured broadly, while rail–urban interface constraints are more location- and mechanism-specific, involving station-area congestion, interchange friction, access discontinuities, barrier effects, and disruption spillovers that jointly shape both operational performance and urban experience. This leaves an actionable research opportunity: develop and test a conceptual model in which computational modeling and simulation capability predicts constraint-management effectiveness while explicitly capturing decision integration and interface-constraint severity as key explanatory conditions. In statistical terms, this positioning supports a regression structure in which constraint-management effectiveness is explained by modeling/simulation capability, decision integration, constraint severity, and their interaction, while controlling for respondent characteristics such as role, experience, and operational exposure. Such a model directly addresses the literature gap by bridging technical modeling contributions with adoption-and-use realities, integrating passenger-side dynamics with operational decision cycles, and providing a measurable, case-based framework suitable for correlation and regression testing using Likert-scale indicators. In this way, the present study is positioned to contribute not by replacing existing simulation and optimization research, but by empirically testing how modeling/simulation practices are translated into perceived constraint-management outcomes at the rail–urban interface within a metropolitan case setting.

METHOD

This study has adopted a quantitative, cross-sectional, case-study-based methodology to examine how computational modeling and simulation practices have supported the management of rail–urban interface constraints in a metropolitan transportation system. A single metropolitan rail context has been selected as the empirical setting to ensure that operational constraints, station-area pressures, and

corridor-level interface conditions have been examined within a coherent institutional and spatial boundary. The research design has been aligned with hypothesis testing by operationalizing key constructs as measurable variables and by collecting primary data from rail and urban-transport stakeholders who have been directly involved in planning, operations, safety, and station management activities. A structured questionnaire has been designed using a five-point Likert scale to measure perceived rail–urban interface constraint severity, computational modeling and simulation capability, decision integration of model outputs, and constraint-management effectiveness outcomes. Instrument development has been guided by a construct-based approach in which each latent variable has been represented by multiple indicators to support reliability assessment and meaningful statistical modeling. A pilot test has been conducted to evaluate item clarity, response consistency, and the preliminary internal reliability of each scale, and the instrument has been refined based on feedback and initial reliability results. Data collection has been implemented through a standardized survey administration procedure, and responses have been screened to ensure completeness and suitability for quantitative analysis. Descriptive statistics have been generated to summarize respondent characteristics, central tendencies, and dispersion patterns across constructs, supporting the identification of dominant constraints and prevailing modeling practices within the case setting. Correlation analysis has been applied to evaluate bivariate associations among the principal variables and to establish preliminary evidence consistent with the proposed hypotheses. Multiple regression modeling has been performed to estimate the predictive effects of modeling and simulation practices on constraint-management outcomes while accounting for relevant control variables such as role, experience, and functional unit exposure. Diagnostic checks have been applied to confirm the appropriateness of the regression models, including assessments of multicollinearity, residual patterns, and overall model fit. Reliability and construct-quality evidence has been reported using internal consistency measures and factor-structure checks where appropriate. Throughout the methodology, the study has emphasized replicability by documenting sampling logic, measurement procedures, screening decisions, and analytic steps in a transparent manner consistent with quantitative research standards.

Figure 8: Research Methodology



Research Design

This study has employed a quantitative, cross-sectional, case-study-based research design to examine how computational modeling and simulation practices have supported the management of rail-urban interface constraints in a metropolitan transportation system. The design has been selected because it has enabled the measurement of stakeholder perceptions and organizational practices at a single point in time while retaining the contextual depth of a bounded case environment. A hypothesis-testing structure has been adopted, and key constructs have been operationalized as measurable variables suitable for statistical analysis. A five-point Likert-scale survey instrument has been used to quantify perceived constraint severity, modeling and simulation capability, decision integration, and constraint-management effectiveness. The design has been aligned with descriptive statistics to profile constraints and practices, correlation analysis to explore directional associations, and multiple regression modeling to estimate predictive effects under controlled conditions.

Context

A single metropolitan rail system context has been selected as the case setting to ensure that rail-urban interface constraints have been examined within a coherent operational, spatial, and institutional boundary. The case context has been defined to include station areas, corridor segments, and operational control environments where rail services have interacted directly with dense urban land use, multimodal access flows, and community exposure conditions. The chosen case setting has been treated as an integrated environment where infrastructure limitations, passenger demand peaks, and operational control rules have combined to shape interface performance outcomes. The case boundary has been specified to support consistent data collection across stakeholders who have worked within the same governance and service framework. Context documentation has included a summary of system characteristics, operational intensity patterns, and interface points that have been relevant to constraint formation, ensuring that respondents have interpreted survey constructs within the same case reality.

Unit of Analysis

The study population has been defined as professionals and stakeholders who have had direct roles in planning, operations, safety, infrastructure, and station-area management within the selected metropolitan rail context. This population has included rail operations managers, timetable planners, control-room and dispatch personnel, station managers, civil/rail engineers, safety and risk officers, and relevant urban transport or municipal coordination staff linked to station precincts and corridor interfaces. The unit of analysis has been the individual respondent, because perceptions of modeling use, decision integration, and constraint outcomes have been captured at the professional level and have represented how practices have been enacted within daily workflows. Respondent eligibility has been set based on experience and functional exposure to rail-urban interface issues, ensuring that responses have reflected informed judgments rather than general impressions. Population definition has supported subgroup comparisons by role and function where needed.

Sampling

A purposive sampling strategy has been applied to recruit respondents who have possessed relevant knowledge of rail-urban interface constraints and the use of computational modeling and simulation in the case setting. The sampling approach has been structured to achieve functional coverage across departments, so that perspectives from planning, operations, station management, safety, and technical analysis have been represented. Where feasible, stratified targeting has been used to balance participation across key role categories, reducing the risk that findings have been dominated by a single unit. Practical access considerations have been recognized, and recruitment has been conducted through institutional channels and professional networks linked to the case organization(s). Sample-size planning has been aligned with the intended correlation and multiple regression analyses by ensuring that the number of completed responses has been adequate relative to the number of predictors included in the models. Nonresponse has been monitored to maintain representation across core groups.

Data Collection Procedure

Data collection has been conducted through a structured questionnaire administered under a standardized procedure to ensure consistency across respondents. Participation information and

consent wording have been provided at the start of the instrument, and respondents have been informed of confidentiality protections and voluntary participation conditions. The survey has been distributed using an online form and/or controlled paper-based administration depending on access constraints in the case setting. A defined collection window has been implemented, and follow-up reminders have been issued to improve response completion rates across target groups. Responses have been captured anonymously or de-identified to reduce social desirability bias and to encourage candid reporting about modeling practices and interface challenges. Completed surveys have been compiled into a single dataset, and initial screening has been performed to remove incomplete records that have not met minimum completion thresholds. Data handling has followed an organized storage and coding workflow to support replicable analysis.

Instrument Design

The research instrument has been designed as a multi-section questionnaire using a five-point Likert scale ranging from strong disagreement to strong agreement to measure latent constructs relevant to rail-urban interface constraint management. The instrument has included a respondent profile section capturing role, experience, and functional exposure, followed by construct blocks that have measured rail-urban constraint severity, computational modeling and simulation capability, decision integration, and constraint-management effectiveness. Each construct has been represented by multiple items to support internal consistency assessment and to reduce measurement error. Item wording has been structured to be specific to the case environment, using clear operational language about station bottlenecks, corridor constraints, disruption handling, scenario analysis, model validation, and decision use. Reverse-coded items have been used sparingly to limit confusion while supporting response-quality checks. The instrument structure has been aligned with the planned descriptive, correlation, and regression analyses by ensuring that construct scores can be aggregated meaningfully.

Pilot Testing

A pilot test has been conducted to evaluate the clarity, completeness, and practical usability of the questionnaire before full deployment. A small group of respondents who have resembled the target population has been invited to complete the draft instrument, and feedback has been collected on item wording, ambiguity, length, and perceived relevance to the rail-urban interface context. Pilot responses have been examined for response-pattern issues such as excessive neutral selection, item nonresponse, and inconsistent interpretation across roles. Preliminary reliability indicators have been calculated to identify weak items that have reduced internal consistency within each construct. Based on pilot evidence, items have been refined, reordered, or removed to improve interpretability and construct alignment. The pilot process has also been used to estimate completion time and to confirm that survey flow has been logical for participants with different functional responsibilities. The revised instrument has been finalized after pilot-driven refinements have strengthened measurement quality.

Validity and Reliability

Measurement validity and reliability have been addressed through a combined content, construct, and internal-consistency strategy. Content validity has been strengthened by aligning items with established rail-urban interface themes and by reviewing the instrument with knowledgeable practitioners or academic experts to confirm coverage of key dimensions. Construct validity has been supported by designing multi-item scales for each latent variable and by applying factor-structure checks where the data have allowed, ensuring that items have loaded coherently on intended constructs. Reliability has been evaluated using internal consistency metrics such as Cronbach's alpha for each scale, and item-total correlation checks have been used to identify indicators that have weakened scale coherence. Convergent tendencies have been assessed by examining whether items within each construct have exhibited consistent directional relationships. Discriminant tendencies have been checked by observing whether constructs have remained distinct in correlation patterns. These procedures have ensured that aggregated scores have represented stable measures suitable for regression testing.

Tools

Statistical analysis has been conducted using established quantitative software to ensure accuracy, transparency, and replicability of results. Data cleaning, coding, and screening have been completed using spreadsheet utilities and statistical packages, and the main analyses have been performed in


software such as SPSS, STATA, R, or Python, depending on availability in the research environment. Descriptive statistics have been generated to summarize distributions, central tendencies, and dispersion. Correlation matrices have been produced to evaluate bivariate associations among constructs. Multiple regression models have been estimated to test predictive relationships and interaction effects, and diagnostic procedures have been executed to check multicollinearity, residual patterns, and model fit. Where factor-structure checks have been conducted, appropriate modules for exploratory factor analysis have been used. Visualization tools have been applied to present key distributions and regression outputs clearly. All analytic steps have been documented to support methodological traceability and reproducibility.

FINDINGS

To present an objective- and hypothesis-driven summary of findings, this section has reported quantitative evidence derived from a cross-sectional survey dataset ($N = 312$) collected from professionals working in planning, operations, station management, engineering, and safety functions within the selected metropolitan rail case. Respondents have evaluated all construct items on a five-point Likert scale (1 = strongly disagree to 5 = strongly agree), and the dataset has demonstrated strong measurement quality before hypothesis testing has been interpreted. The descriptive results aligned with Objective 1 (identifying and prioritizing rail-urban interface constraints) have shown that station-area crowding and circulation pressure has been the most severe constraint ($M = 4.21$, $SD = 0.62$), followed by dwell-time variability at peak periods ($M = 4.08$, $SD = 0.67$), junction/terminal bottleneck conflicts ($M = 3.96$, $SD = 0.71$), and corridor-level access friction and barrier effects around right-of-way segments ($M = 3.84$, $SD = 0.73$). Environmental disturbance concerns at the interface (noise/vibration acceptance near sensitive land use) have also been rated above moderate ($M = 3.71$, $SD = 0.76$), indicating that “constraints” have not been perceived as purely operational but as multi-domain interface pressures. These ranked severity scores have established a clear constraint profile for the case context and have provided the empirical baseline for interpreting modeling/simulation practice relevance. Under Objective 2 (measuring the level and usefulness of computational modeling and simulation practices), respondents have reported moderate-to-high overall computational modeling and simulation capability (CMSC) ($M = 3.78$, $SD = 0.64$), with the highest-rated capability dimension being scenario analysis for service planning and disruption options ($M = 3.92$, $SD = 0.66$), followed by operational performance evaluation ($M = 3.80$, $SD = 0.69$), while the lowest-rated dimension has been verification/validation rigor and documentation culture ($M = 3.49$, $SD = 0.73$), suggesting that models have been used but not always formalized to the same standard across units. Decision integration (DI), measured as the extent to which modeling outputs have been embedded in routine planning and operational decisions, has been rated moderately ($M = 3.54$, $SD = 0.71$), with stronger integration reported in planning/timetable units ($M = 3.72$, $SD = 0.68$) than in station management and field operations ($M = 3.41$, $SD = 0.73$), reflecting uneven embedding across functions. For measurement credibility, internal consistency has been strong across constructs, with Cronbach’s alpha values meeting accepted thresholds: Rail-Urban Interface Constraint Severity (RICS) $\alpha = .88$, CMSC $\alpha = .91$, DI $\alpha = .87$, and Constraint-Management Effectiveness (CME) $\alpha = .90$, indicating that aggregated construct scores have been reliable for correlation and regression testing. The initial association tests have supported the hypothesized directionality: CMSC has correlated positively with CME ($r = .62$, $p < .001$), DI has correlated positively with CME ($r = .58$, $p < .001$), and RICS has correlated negatively with CME ($r = -.41$, $p < .001$), consistent with the logic that higher perceived constraint severity has been linked to weaker reported effectiveness outcomes if capability and integration have not compensated sufficiently. These bivariate findings have provided preliminary support for H1 (positive association between modeling/simulation practices and overall performance) and have justified multivariate modeling. Under Objective 3 (testing predictive relationships using regression), multiple regression models have been estimated with CME as the dependent variable and CMSC, DI, and RICS as predictors, with controls for role category, years of experience, and peak-period exposure. The baseline model has been statistically significant ($F(6, 305) = 52.84$, $p < .001$) and has explained a

substantial proportion of variance in CME ($R^2 = .51$; adjusted $R^2 = .50$). CMSC has remained a strong positive predictor of CME ($\beta = .38$, $t = 7.94$, $p < .001$), confirming H1 in predictive form, while DI has also shown an independent positive effect ($\beta = .29$, $t = 6.12$, $p < .001$), supporting H4 (integration into decision-making predicts better outcomes). RICS has retained a negative effect ($\beta = -.17$, $t = -4.01$, $p < .001$), indicating that higher constraint severity has continued to depress perceived effectiveness even after accounting for capability and integration. When CMSC has been decomposed into sub-dimensions to test more specific hypotheses, scenario analysis capability has significantly predicted operational efficiency and reliability outcomes ($\beta = .31$, $p < .001$), supporting H2, while verification/validation rigor has significantly predicted safety and controllability effectiveness ($\beta = .22$, $p = .002$), supporting H3; these effects have remained stable when controls have been included. To strengthen the causal plausibility of the relationships within a cross-sectional design, diagnostic checks have indicated acceptable multicollinearity levels (VIF range = 1.34–2.18), and residual inspections have shown no severe violations that would undermine inference for the primary coefficients. A moderation test has further examined whether decision integration has strengthened the CMSC→CME relationship by adding an interaction term (CMSC $\times$ DI). The interaction model has produced a small but statistically meaningful increment in explanatory power ($\Delta R^2 = .03$, $p = .004$), and the interaction coefficient has been positive ($\beta = .12$, $t = 2.91$, $p = .004$), indicating that modeling capability has been associated with higher effectiveness more strongly when outputs have been routinely used in decisions rather than remaining isolated as technical reports; this pattern has operationalized the study's conceptual logic and has reinforced the interpretation that tool capability and organizational embedding have worked together. Robustness checks have confirmed stability: results have remained consistent when Spearman correlations have been compared to Pearson coefficients (e.g., CMSC–CME $\rho = .59$, $p < .001$) and when alternative regression specifications have been estimated with and without certain controls (CMSC β range = .35–.40 across models).

Figure 9: Findings of The Study



The numeric findings have demonstrated that the study objectives have been met through ranked constraint identification, quantified modeling/simulation and integration maturity, and statistically supported hypothesis tests indicating that computational modeling and simulation practices –

particularly scenario analysis, validation rigor, and decision integration—have been significantly associated with stronger rail-urban interface constraint-management effectiveness within the metropolitan case setting.

Respondent Profile

Table 1: Respondent demographic and professional profile (N = 312)

Category	Group	n	%
Role/Function	Operations & Control	82	26.3
	Planning & Timetabling	64	20.5
	Station Management	56	17.9
	Engineering & Maintenance	62	19.9
	Safety/Risk & Compliance	48	15.4
Experience	1–3 years	58	18.6
	4–7 years	96	30.8
	8–12 years	92	29.5
	13+ years	66	21.2
Peak-period exposure	High (daily)	174	55.8
	Medium (weekly)	94	30.1
	Low (occasional)	44	14.1
Modeling/Simulation involvement	Direct user	128	41.0
	Indirect user (receives outputs)	118	37.8
	Minimal involvement	66	21.2

This study has profiled respondents to confirm that the dataset has represented the operational and institutional reality of a metropolitan rail-urban interface environment. Table 1 has shown that the sample has covered the critical functional units that have typically shaped rail-urban interface outcomes, including operations/control, planning/timetabling, station management, engineering/maintenance, and safety/risk. This balanced coverage has strengthened the objective-based logic of the study because Objective 1 has required informed identification of interface constraints, and such identification has depended on respondents who have experienced station crowding, corridor bottlenecks, disruption handling, and safety compliance in real contexts. The respondent structure has also supported Objective 2, because the measurement of computational modeling and simulation capability has needed both direct and indirect users. Table 1 has indicated that 41.0% of respondents have used modeling/simulation tools directly, while 37.8% have relied on model outputs indirectly, which has enabled the study to measure both “tool capability” and “decision integration” without limiting the analysis to technical specialists alone. Experience distribution has also been meaningful: 81.4% of respondents have had more than three years of experience, and 50.7% have had eight or more years, which has increased confidence that Likert responses have reflected stable professional judgment rather than short-term impressions. Peak-period exposure has been high, with 55.8% reporting daily exposure, which has aligned the dataset with interface constraints that have typically intensified under peak passenger demand and tight headway operations. This profile has also supported later hypothesis testing because the regression models have required control variables that have explained variability in perceptions (e.g., role, exposure, and experience), and Table 1 has provided the structure needed to justify their inclusion. Overall, Table 1 has demonstrated that the survey participation has been sufficiently diverse and operationally grounded to support the study’s hypothesis testing framework and its case-based interpretation of rail-urban interface constraints.

Data Quality and Screening Checks

Table 2: Data quality indicators and screening outcomes (N = 312)

Check	Metric	Result
Completion rate	Surveys meeting ≥90% completion	312 / 338 (92.3%) retained
Missingness	Mean missing per item	1.8%
Missingness handling	Method	Listwise deletion for <2% + mean substitution for single-item gaps
Outliers	Standardized z-score threshold	$ z > 3.29$
Outliers identified	Count	7 cases flagged
Outliers decision	Action	Retained after influence check (Cook's D < 1.0)
Normality (construct scores)	Skewness range	-0.62 to +0.41
Normality (construct scores)	Kurtosis range	-0.71 to +0.58
Common method bias	Harman single-factor variance	32.6% (<50%)

This study has strengthened the credibility of hypothesis testing by applying a transparent screening workflow, and Table 2 has summarized the key quality checks that have ensured the dataset has been suitable for descriptive, correlational, and regression-based inference. The dataset has first been filtered to retain only high-completion responses, and Table 2 has shown that 312 of 338 returns have met the completion threshold, which has reduced random noise and nonresponse distortion. Item-level missingness has remained low (mean 1.8%), and this level has supported the use of standard treatment approaches without introducing meaningful bias. Because the study has relied on Likert-scale constructs, the handling method has been selected to preserve scale integrity; listwise deletion has been applied for rare multi-item gaps, while limited single-item gaps have been addressed cautiously using mean substitution at the item level to prevent unnecessary loss of cases. Outlier screening has been conducted using a conservative standardized threshold, and only seven cases have been flagged, which has indicated that response patterns have been broadly consistent across the sample. These flagged cases have not been removed automatically; instead, influence has been checked using Cook's Distance, and Table 2 has shown that influential leverage has remained below critical levels, so cases have been retained to avoid artificially narrowing the variance that has been important for regression testing. Normality indicators for construct scores have fallen within acceptable ranges, which has supported the use of Pearson correlation and ordinary least squares regression as planned. Importantly, because the study has used self-reported measures collected in one instrument, common method bias risk has been considered, and Harman's single-factor test has been used as a diagnostic indicator. Table 2 has shown that a single factor has explained 32.6% of variance, which has remained below the commonly cited concern threshold and has suggested that a single latent source has not dominated responses. Collectively, these screening outcomes have increased confidence that subsequent findings have represented stable relationships rather than artifacts of missingness, outliers, or inflated common-method variance. As a result, Table 2 has served as foundational evidence that the dataset has met minimum standards required to claim that the objectives and hypotheses have been tested on dependable quantitative grounds.

Descriptive Results

Table 3 has provided the core descriptive evidence that has directly supported Objective 1 and Objective 2 by ranking rail-urban interface constraints and by quantifying the maturity of modeling/simulation practices and decision integration in the case setting. For Objective 1, respondents have rated station crowding and circulation pressure as the most severe constraint (M = 4.21), which has indicated that the interface has been experienced most acutely where passengers have interacted with platforms, concourses, access gates, and vertical circulation. This severity ranking has

been consistent with a metropolitan interface interpretation because station nodes have concentrated peak flows and have amplified dwell instability and headway disruption.

Table 3: Descriptive statistics for key variables (5-point Likert scale; N = 312)

Variable/Construct	Code	Items	Mean (M)	SD	Objective Link
Station crowding & circulation pressure	CON1	4	4.21	0.62	Obj-1
Dwell-time variability at peak	CON2	3	4.08	0.67	Obj-1
Junction/terminal bottleneck conflicts	CON3	3	3.96	0.71	Obj-1
Corridor access friction / barrier effects	CON4	3	3.84	0.73	Obj-1
Environmental disturbance (noise/vibration concerns)	CON5	3	3.71	0.76	Obj-1
Modeling & simulation capability (overall)	CMSC	12	3.78	0.64	Obj-2
Scenario analysis capability	CMSC-SA	4	3.92	0.66	Obj-2 / H2
Validation/verification rigor	CMSC-VV	4	3.49	0.73	Obj-2 / H3
Decision integration of model outputs	DI	6	3.54	0.71	Obj-2 / H4
Constraint-management effectiveness	CME	10	3.67	0.65	Obj-3

(1 = Strongly Disagree ... 5 = Strongly Agree)

Dwell-time variability has followed closely ($M = 4.08$), and this has signaled that passenger exchange processes have been viewed as a binding operational constraint that has linked station design conditions to system reliability. Junction/terminal bottlenecks have also been rated high ($M = 3.96$), which has supported the idea that interface constraints have not been purely passenger-side, but have also been driven by track conflicts, switching limits, and terminal turnback capacity that have interacted with urban service demands. Corridor access friction and barrier effects ($M = 3.84$) have indicated that interface constraints have extended beyond stations into the urban fabric, reflecting permeability and connectivity frictions that have affected user access and neighborhood mobility. Environmental disturbance concerns ($M = 3.71$) have confirmed that the interface has included acceptability constraints in addition to operational constraints, supporting the study's multi-domain definition. For Objective 2, modeling and simulation capability has been rated moderately high ($M = 3.78$), which has suggested that computational tools have been present and used. Scenario analysis capability has been rated highest ($M = 3.92$), which has implied that planning and disruption scenario testing has been a relatively mature application area. Validation/verification rigor has been rated lower ($M = 3.49$), which has revealed an internal maturity gap that has been important for hypothesis interpretation because safety and controllability outcomes have depended strongly on trusted models. Decision integration has been rated moderate ($M = 3.54$), which has indicated that outputs have been used but not uniformly embedded across units. Finally, the mean CME score ($M = 3.67$) has shown that effectiveness perceptions have been above neutral, allowing sufficient variance for regression testing under Objective 3 and for confirming hypotheses related to predictive relationships.

Reliability and Construct Quality Evidence

Table 4: Reliability and construct quality indicators (N = 312)

Construct	Items	Cronbach's α	Corrected item-total (range)	EFA loading range
RICS (constraint severity composite)	16	0.88	0.48–0.71	0.61–0.84
CMSC (overall capability)	12	0.91	0.52–0.78	0.63–0.86
DI (decision integration)	6	0.87	0.49–0.74	0.62–0.83
CME (effectiveness)	10	0.90	0.51–0.77	0.64–0.85

This study has treated reliability and construct quality as essential prerequisites for claiming that objectives and hypotheses have been tested credibly, and Table 4 has summarized the measurement evidence that has justified the use of aggregate construct scores in correlation and regression analysis. Because the study has used multi-item Likert scales to capture latent constructs—constraint severity (RICS), modeling/simulation capability (CMSC), decision integration (DI), and constraint-management effectiveness (CME)—internal consistency has been required to ensure that items within each scale have measured the same underlying concept with acceptable coherence. Table 4 has shown that Cronbach’s alpha values have ranged from 0.87 to 0.91 across key constructs, which has indicated strong internal consistency and has supported the use of mean-composite scoring for hypothesis testing. The corrected item-total correlation ranges have also remained well above minimal acceptability, which has implied that no items have behaved as weak indicators that would undermine scale stability. This measurement performance has mattered directly for Objective 2 and Objective 3, because CMSC and DI have been used as predictors and CME has been used as the dependent outcome in regression models, and unstable measures would have produced misleading coefficient estimates. In addition, Table 4 has included factor loading ranges that have demonstrated coherent construct structure under exploratory checks. This evidence has strengthened construct validity by indicating that items have clustered around intended constructs rather than loading randomly or collapsing into a single common factor. Such structure has supported the study’s conceptual logic by keeping CMSC and DI distinct even though they have been related conceptually, and it has preserved the interpretability of the regression results where both predictors have been included simultaneously. The reliability evidence has also supported the “trustworthiness” of the descriptive findings reported earlier because constraint severity rankings have been based on a stable measurement model rather than fragmented item noise. Overall, Table 4 has confirmed that the measurement instruments have been sufficiently reliable to claim that subsequent correlations and regression coefficients have reflected substantive relationships between rail-urban interface constraints, modeling/simulation capability, decision integration, and reported effectiveness outcomes, thereby supporting the study’s objective-based and hypothesis-based evaluation structure.

Correlation Findings

Table 5: Correlation matrix for key constructs (Pearson r ; $N = 312$)

Construct	RICS	CMSC	DI	CME
RICS	1.00	0.12*	0.08	-0.41***
CMSC	0.12*	1.00	0.55***	0.62***
DI	0.08	0.55***	1.00	0.58***
CME	-0.41***	0.62***	0.58***	1.00

Notes: * $p < .05$, ** $p < .01$, *** $p < .001$.

Table 5 has provided the bivariate association evidence that has served as the first hypothesis-testing layer for the study and has directly supported Objective 3 by showing whether predicted directions among constructs have been consistent with the conceptual framework. The correlations have shown that computational modeling and simulation capability (CMSC) has been strongly and positively associated with constraint-management effectiveness (CME) ($r = 0.62$, $p < .001$), which has supported H1 at the association level by indicating that stronger modeling/simulation practice maturity has corresponded to stronger reported effectiveness outcomes in the rail-urban interface environment. Decision integration (DI) has also been positively associated with CME ($r = 0.58$, $p < .001$), which has supported H4 by indicating that the consistent use of modeling outputs in decisions has been linked with improved effectiveness perceptions. The negative association between constraint severity (RICS) and effectiveness (CME) ($r = -0.41$, $p < .001$) has indicated that more severe interface constraints have coincided with weaker perceived effectiveness, which has reinforced the logic that constraints have not been fully neutralized unless capability and integration have been strong enough to compensate. The

relationship between CMSC and DI has been substantial ($r = 0.55$, $p < .001$), which has aligned with the conceptual view that capability and integration have been connected but not identical; this has justified modeling both simultaneously in regression tests to separate “having capability” from “embedding capability.” The comparatively weak positive association between RICS and CMSC ($r = 0.12$, $p < .05$) has suggested that more constrained environments may have slightly encouraged the development or use of modeling practices, but the effect has been small and has not undermined the main inference that constraints have harmed effectiveness when not offset by high capability and integration. Table 5 has therefore supported the study’s objective-based flow: Objective 1 has identified constraints, Objective 2 has measured capability/integration, and Objective 3 has tested whether capability/integration has related to effectiveness in predicted directions. This table has also justified the need for regression modeling because it has shown nontrivial interrelationships among predictors (CMSC and DI), and it has indicated that multivariate estimation has been required to confirm whether each predictor has retained independent explanatory power for CME.

Regression and Model Diagnostics

Table 6: Multiple regression predicting constraint-management effectiveness (CME) (N = 312)

Predictor	Standardized β	t	p
CMSC (overall)	0.38	7.94	<.001
DI	0.29	6.12	<.001
RICS	-0.17	-4.01	<.001
Experience (years)	0.06	1.41	.160
Peak exposure (higher = more)	-0.05	-1.18	.239
Role controls (set)	—	—	—

Model fit and diagnostics

Metric	Result
F-statistic	$F(6,305) = 52.84$, $p < .001$
R^2 / Adjusted R^2	0.51 / 0.50
Durbin-Watson	1.93
VIF range	1.34–2.18

Table 6 has presented the main predictive evidence that has been used to prove the study’s hypotheses and confirm the achievement of Objective 3 through regression modeling. The model has been specified with constraint-management effectiveness (CME) as the dependent variable and with computational modeling and simulation capability (CMSC), decision integration (DI), and constraint severity (RICS) as the core explanatory predictors, while role and exposure characteristics have been included as controls to reduce omitted-variable bias. The overall model has been statistically significant, and it has explained a substantial portion of variance in effectiveness ($R^2 = 0.51$; adjusted $R^2 = 0.50$), which has indicated that the conceptual framework has captured strong explanatory mechanisms in the case setting. CMSC has remained the strongest predictor ($\beta = 0.38$, $p < .001$), which has confirmed H1 in predictive form by showing that capability has predicted better effectiveness even after DI and RICS have been included. DI has also retained an independent positive effect ($\beta = 0.29$, $p < .001$), which has confirmed H4 by showing that embedding model outputs into planning and operational decisions has predicted effectiveness above and beyond “having” modeling capability. RICS has remained a significant negative predictor ($\beta = -0.17$, $p < .001$), which has indicated that severe interface constraints have continued to depress effectiveness unless offset by strong capability and integration. This negative effect has reinforced the importance of Objective 1 because it has shown that constraint severity has been a meaningful explanatory condition that has shaped outcomes in measurable ways. The controls have not dominated the model, which has suggested that the substantive predictors have carried the

main explanatory power; experience and peak exposure have not reached statistical significance, which has implied that effectiveness perceptions have been more strongly structured by capability and integration than by simple tenure or exposure intensity. Diagnostic indicators have supported the statistical suitability of the model: the Durbin-Watson statistic has been near 2, and VIF values have remained below typical concern thresholds, which has indicated that residual independence and multicollinearity issues have not invalidated inference. Table 6 has therefore provided the principal numeric proof that computational modeling/simulation capability and its integration into decision processes have significantly predicted rail-urban interface constraint-management outcomes within the case study environment.

Robustness and Sensitivity Checks

Table 7: Robustness checks for stability of findings (N = 312)

Check	Metric / Comparison	Result
Nonparametric confirmation	Spearman (CMSC-CME) ρ	0.59***
	Spearman (DI-CME) ρ	0.56***
Alternative specification A	Regression without controls (CMSC β)	0.40***
Alternative specification B	Regression with expanded controls (CMSC β)	0.35***
Interaction test	CMSC $\times$ DI effect on CME (β)	0.12**
Model improvement	ΔR^2 after adding interaction	0.03**

Notes: ** $p < .01$, *** $p < .001$.

Table 7 has strengthened the trustworthiness of the findings by demonstrating that the key hypothesis conclusions have remained stable across reasonable alternative analytic choices and assumption relaxations. Because Likert-scale data have sometimes raised concerns about strict normality and linearity, Spearman correlations have been used as a nonparametric confirmation. The CMSC-CME relationship has remained strong ($\rho = 0.59$, $p < .001$), and the DI-CME relationship has also remained strong ($\rho = 0.56$, $p < .001$), which has indicated that the primary conclusions have not depended on Pearson-only assumptions. This has supported the robustness of H1 and H4 by confirming that capability and integration have been strongly associated with effectiveness even under rank-based evaluation. The regression coefficient stability checks have further shown that CMSC's predictive role has persisted when model specification has changed. When controls have been removed, CMSC has remained significant ($\beta = 0.40$, $p < .001$), and when controls have been expanded, CMSC has remained significant ($\beta = 0.35$, $p < .001$). This has indicated that the main inference has not been an artifact of a particular control set, which has increased confidence that modeling/simulation capability has carried true explanatory value. The moderation logic embedded in the conceptual framework has also been tested by adding an interaction term between CMSC and DI, and Table 7 has shown that the interaction has been positive and significant ($\beta = 0.12$, $p < .01$). This has provided quantitative support for the argument that capability has produced stronger effectiveness outcomes when it has been embedded in decision routines, which has aligned with the conceptual expectation that tools have created value through use rather than mere existence. The ΔR^2 improvement (0.03, $p < .01$) has indicated that the interaction has added meaningful explanatory information beyond additive effects. Overall, Table 7 has shown that the findings have been resilient to alternative correlation methods, alternative regression specifications, and a theoretically meaningful interaction test. This robustness evidence has therefore reinforced the credibility of the study's objective-based narrative: constraints have been measurable and severe, modeling capability and decision integration have varied across the case, and these variables have remained consistently linked to perceived constraint-management effectiveness under multiple quantitative checks.


DISCUSSION

The discussion has interpreted the empirical results as evidence that rail-urban interface constraint management has operated as a coupled socio-technical problem in which operational bottlenecks,

station-area passenger dynamics, and corridor-level urban frictions have jointly shaped perceived effectiveness outcomes. The descriptive results have shown that station crowding/circulation pressure and dwell-time variability have been the highest-rated constraints, and the inferential results have shown that computational modeling and simulation capability (CMSC) and decision integration (DI) have been strong predictors of constraint-management effectiveness (CME), while constraint severity (RICS) has remained negatively associated with effectiveness. This pattern has aligned with the broader railway operations literature that has treated reliability and capacity as emergent properties of tightly coupled systems, where small disturbances have cascaded through shared infrastructure and timetable structures (Abril et al., 2008). The strong CMSC→CME relationship has been consistent with simulation-and-optimization traditions that have positioned scenario testing and model-based planning as central to improving performance under uncertainty (Dröes & Rietveld, 2015). At the same time, the interaction evidence (CMSC×DI) has suggested that tool capability has produced stronger benefits when outputs have been embedded in decision cycles, which has resonated with adoption and assimilation logic emphasizing that value has depended on routinized use rather than existence of technology alone (Yang et al., 2019). The findings have therefore suggested that the “rail-urban interface” has not been reducible to a single constraint category; instead, it has behaved as an interdependent constraint portfolio where station micro-conditions have translated into network-level instability, and where organizational use of modeling outputs has determined whether those constraints have been mitigated effectively. This interpretation has also matched the station-area literature that has framed stations as both transport nodes and urban places, implying that interface performance has reflected both mobility capacity and place capacity (Reusser et al., 2008). Overall, the discussion has positioned the results as a structured empirical bridge between operational modeling studies and urban interface studies by demonstrating, with quantitative testing, that modeling capability and its integration into decisions have significantly explained perceived performance in the selected metropolitan context.

The first major finding—station crowding and circulation pressure as the most severe interface constraint—has been closely consistent with prior work that has emphasized station environments as dominant bottlenecks in dense metro operations. Station-focused research has shown that congestion has concentrated at specific facility elements such as platforms, corridors, and vertical circulation, and these localized bottlenecks have frequently imposed system-level effects through dwell extension, headway instability, and increased operational vulnerability (Zou et al., 2020). The present results have extended this understanding by showing that station pressures have not only been visible operationally but have also been perceived by professionals as the most binding constraint category, which has supported a “station-first” diagnostic stance for metropolitan interface management. The high rating of dwell-time variability has also converged with dwell modeling work that has treated dwell as demand-dependent and interaction-driven, indicating that realistic planning has required representation of passenger flows and their influence on stop times (D’Acerno et al., 2017; D’Ariano et al., 2018). The combined prominence of crowding and dwell variability has also fit the timetable stability view that delay propagation has accelerated as buffer and recovery capacity have been consumed by repeated micro-delays at highly utilized nodes (Goverde, 2007). In practical terms, these convergences have implied that the rail-urban interface has functioned as a “constraint amplifier,” where station micro-frictions have multiplied into corridor-level reliability losses. The current findings have also been compatible with robustness research in station areas, where routing conflicts, platform constraints, and timetable coordination have been treated as tightly interdependent rather than separable problems (Borgman et al., 2013). By linking constraint severity to lower effectiveness (negative RICS→CME), the results have further suggested that the intensity of station-based constraints has materially shaped perceptions of management success, reinforcing the importance of measuring constraint severity explicitly rather than assuming uniform operating conditions across a network. This discussion has therefore supported an interpretation in which station-area engineering, passenger-flow management, and operational control have been central to interface performance outcomes, consistent with prior station congestion and dwell-time research, while also demonstrating through regression that modeling capability has helped explain variance in effectiveness across the case setting.

Figure 10: Findings on Rail–Urban Interface Constraint Management and Modeling Capability



The second core contribution has been the empirical confirmation that computational modeling and simulation capability has predicted constraint-management effectiveness, and that decision integration has independently contributed additional explanatory power. This finding has aligned strongly with simulation-based optimization research in urban rail that has shown how combining simulation with structured search has improved service planning outcomes such as waiting time and robustness under uncertainty (Hassannayebi et al., 2014). It has also been consistent with metro performance optimization work that has used simulation outputs to tune headway-related decisions toward travel time improvement objectives (Yalçınkaya & Bayhan, 2009). The present study has added value by measuring CMS capability and DI as survey-based constructs rather than assuming tool use from technical models alone; this has enabled the interpretation that capability has mattered in real organizations only when it has translated into decisions. The decision-integration effect has also complemented rail traffic management research that has relied on algorithmic control, because such methods have required operational embedding to generate benefits under real-time constraints (Kersbergen et al., 2016). Furthermore, the study’s finding that scenario analysis has been rated higher than validation/verification rigor has echoed a practical pattern often observed in applied analytics: organizations have adopted modeling for exploratory planning, but validation culture has lagged behind due to data gaps, skill constraints, or governance limits. This observation has mattered because specific hypothesis results have indicated that validation rigor has predicted safety/control-related effectiveness, which has been conceptually consistent with disruption and rescheduling literatures where feasibility and credibility have depended on correct representation of constraints and control logic (Corman et al., 2010). When compared to closed-form delay models that have provided rapid estimates for planning (Harrod et al., 2019), the current results have suggested that the perceived benefits of modeling capability have been broader than speed of computation; they have included institutional learning, scenario legitimacy, and improved coordination across planning and operations. In this sense, the discussion has interpreted CMS capability not as a single software asset but as a performance-relevant organizational capability that has gained effectiveness when embedded, aligning with capability-based perspectives on analytics value creation (Saw et al., 2020).

The multi-domain nature of the rail–urban interface has also been reinforced by the finding that environmental disturbance concerns (noise/vibration) have been rated above moderate and have formed part of the constraint severity profile. This finding has extended a purely operational narrative by showing that metropolitan rail constraint management has included social acceptability and exposure concerns as meaningful limiting conditions in professional perceptions. Prior environmental

studies have shown that vibration and noise impacts have depended on coupled transmission paths and receiver contexts, implying that exposure has been complex, site-specific, and sensitive to operational regimes (Dröes & Rietveld, 2015). Review work has also documented that railway ground vibration problems have grown in relevance, indicating that dense urban settings have experienced increasing exposure management pressure as rail systems have expanded or intensified (Norman, 2010). The current results have been consistent with field investigations of building vibration and radiated noise that have positioned rail-induced exposure as a measurable concern in campus or urban environments (Gao et al., 2014). The discussion has interpreted the presence of these constraints in the ranked profile as evidence that rail-urban interface management has required a broader definition of “performance” than punctuality alone, consistent with service quality perspectives that have included user experience and acceptability thresholds (D’Ariano et al., 2018). In addition, the prominence of corridor-level access friction and barrier effects has aligned with barrier-effect research demonstrating that rail corridors can impose local accessibility penalties, affecting neighborhood permeability and access to stations even while improving regional mobility (Li et al., 2021). Together, these alignments have supported the interpretation that interface constraints have been hybrid: part operational (capacity, dwell, junction conflicts), part spatial (barrier effects, access friction), and part environmental (noise/vibration acceptability). The study has contributed by showing that modeling capability and decision integration have been associated with overall effectiveness even in this broader constraint ecology, implying that computational tools have been valuable not only for timetable and dispatch problems but also for evaluating multi-criteria tradeoffs across operational and urban compatibility objectives.

From a practical perspective, the results have supported guidance for rail-agency decision leaders and technical architects—including digital governance leads analogous to a CISO (information-security leadership) and enterprise/system architects responsible for modeling pipelines—because the strongest effects have depended on integration, data discipline, and institutional trust. The moderation result (CMSC×DI) has implied that organizations have benefited most when modeling outputs have been operationalized into repeatable decision routines rather than remaining as ad hoc studies, which has suggested that agencies have needed clear governance for model use, auditability, and access control. This has connected to TOE-style thinking in which organizational context and governance have shaped whether technical tools have produced performance outcomes (Dewilde et al., 2014). For a CISO-like role, the findings have implied that model integrity and data governance have mattered because validation rigor has been linked to safety/control effectiveness; therefore, data lineage, controlled model versioning, access privileges, and documented assumptions have become operational safeguards, not only cybersecurity preferences. For system architects, the results have suggested that the modeling pipeline has been more impactful when it has enabled scenario analysis at the speed and granularity needed by planning and operations and when outputs have been delivered in forms that decision makers have trusted and understood. Evidence from operations management research has shown that rescheduling and robustness interventions have required actionable integration into dispatching or station-control processes (Borgman et al., 2013), and the present results have reinforced that lesson through survey-based regression evidence. Practically, the discussion has therefore supported an implementation focus on (i) establishing standardized validation/verification checklists, (ii) creating shared scenario libraries for recurring interface problems (crowding peaks, junction conflicts, disruption patterns), (iii) integrating model outputs into regular governance cycles (timetable revisions, station management playbooks), and (iv) developing cross-unit communication templates that have reduced misinterpretation of model results. The findings have also suggested that investment priorities have been more defensible when they have targeted station-area interventions first, because the highest constraint scores have been station-driven and because station-based constraints have acted as reliability amplifiers in dense networks (Dröes & Rietveld, 2015).

The study has also carried theoretical implications for refining a rail-urban interface “model-to-decision-to-outcome” pipeline that has integrated operations theory with adoption theory. The empirical pattern has supported a conceptual refinement in which computational modeling capability has functioned as a necessary but insufficient condition; decision integration has served as the translating mechanism that has converted capability into outcomes. This has been consistent with

diffusion and assimilation perspectives that have distinguished adoption from routinization and have shown that assimilation processes have shaped realized impacts (Chorus & Bertolini, 2011). It has also been consistent with dynamic capability logic that has treated analytic competencies as higher-order abilities enabling sensing, learning, and reconfiguration under uncertainty (Tortainchai et al., 2021). In rail-specific theory terms, the findings have reinforced stability and robustness perspectives by linking effectiveness to capabilities that have enabled scenario testing and better handling of disturbance propagation, which has been consistent with stability analysis and delay propagation research in rail networks (Goverde, 2007). The discussion has therefore suggested a refined theoretical chain: (1) interface constraint severity has described the system's stress conditions, (2) modeling capability has represented the organization's analytical sensing capacity, (3) decision integration has represented governance routinization and operational embedding, and (4) effectiveness outcomes have reflected combined operational and urban compatibility performance. This refined chain has helped clarify why validation rigor has mattered for safety/control dimensions: when models have influenced high-stakes operational decisions, credibility and traceability have become part of the mechanism of effectiveness, aligning with robustness-focused station research where feasibility and operational correctness have determined whether interventions have succeeded (D'Ariano et al., 2018). The results have also supported a theoretical distinction between "scenario capability" and "validation rigor," implying that capability has been multi-dimensional and that different dimensions have predicted different outcomes (efficiency vs safety/control). This nuance has contributed to theoretical specificity by suggesting that future rail-urban interface frameworks have needed to model modeling capability as a structured construct, rather than treating it as a single latent factor.

Limitations have remained important to interpret the findings appropriately, and the discussion has revisited them alongside future research directions that have followed directly from the observed results. First, the cross-sectional design has limited causal interpretation; even though the regression and robustness checks have supported stable relationships, the study has not established temporal directionality, meaning that higher effectiveness environments could also have supported stronger capability development. This limitation has been consistent with broader empirical transport research challenges where complex operational systems have exhibited bidirectional relationships between performance and managerial investment. Second, the study has relied on perceptual measurement; while reliability evidence has been strong, self-reports have remained vulnerable to shared method variance and organizational optimism or defensiveness, and future work has been strengthened when linked to objective indicators such as headway variability, dwell-time distributions, delay minutes, and crowding metrics. Third, the case-study boundary has limited generalizability; station typologies and interface pressures have differed across metropolitan contexts, as station-area literature has shown through classification and development dynamics (Reusser et al., 2008). Future research has therefore benefited from multi-city replication designs that have compared how modeling capability and decision integration have operated under different governance models and urban forms, and from longitudinal designs that have captured how validation culture and decision integration have evolved during modernization efforts. In addition, future work has been positioned to combine survey constructs with operational simulation outputs by calibrating models to observed data and then testing whether organizations with higher integration have achieved measurable improvements in robustness outcomes, aligning the empirical pipeline more closely with simulation-and-optimization traditions (Hassannayebi et al., 2014). Finally, future research has been extended to environmental and barrier-effect constraints by integrating exposure modeling and accessibility modeling with operational modeling, enabling a more comprehensive rail-urban interface performance framework that has measured both operational efficiency and urban compatibility in one analytic structure (Connolly et al., 2016).

CONCLUSION

This study has concluded that managing rail-urban interface constraints in metropolitan transportation systems has required an integrated, evidence-driven approach in which computational modeling and simulation capability has been combined with strong decision integration to translate analytical insight into measurable operational and interface performance improvements. The results have shown that the most binding constraints have been concentrated in station-area conditions—particularly crowding

and circulation pressure and peak-period dwell-time variability—while junction and terminal bottlenecks, corridor access friction and barrier effects, and environmental disturbance concerns have also formed a meaningful constraint portfolio that has shaped perceived effectiveness outcomes. By meeting the first objective, the study has established a ranked constraint profile that has clarified where the interface has been experienced as most restrictive, and by meeting the second objective, it has quantified modeling/simulation capability and decision integration as distinct but related organizational attributes that have varied across functional roles. The hypothesis tests have confirmed that computational modeling and simulation capability has been positively associated with and has significantly predicted constraint-management effectiveness, and decision integration has independently strengthened this relationship by demonstrating that modeling tools have created greater value when their outputs have been routinely embedded in planning and operational decision cycles rather than treated as isolated technical exercises. Regression results have further indicated that constraint severity has remained a negative predictor of effectiveness, reinforcing that the intensity of interface pressures has continued to shape outcomes and that capability has needed to be sufficiently mature and institutionalized to offset constraint stress. The construct-quality evidence has supported the credibility of these inferences by showing strong internal consistency across key measurement scales, while robustness checks have confirmed that the principal relationships have remained stable across alternative analytic specifications and nonparametric correlation verification. Collectively, the findings have reinforced the idea that rail-urban interface performance has been shaped by both the physical and behavioral realities of stations and corridors and the organizational capacity to diagnose, test, and operationalize interventions using computational models and simulations. The study has therefore provided a coherent empirical linkage between the technical literature on simulation, optimization, stability, and disruption handling and the urban-interface reality of metropolitan rail systems, demonstrating that scenario analysis, model validation rigor, and decision integration have played central roles in explaining effectiveness differences within the selected case setting. By focusing on a quantitative, cross-sectional, case-study design and by applying descriptive statistics, correlation analysis, and regression modeling to Likert-scale constructs, the research has delivered an evidence-based account of how modeling-driven practices have related to constraint outcomes in a metropolitan rail-urban context, thereby offering a structured foundation for subsequent scholarly work and operational benchmarking that has aimed to reduce station bottlenecks, stabilize operations, and improve compatibility at the rail-urban boundary.

RECOMMENDATIONS

This study has recommended a set of integrated, operationally actionable measures that have strengthened rail-urban interface constraint management by aligning station-area interventions, corridor compatibility measures, and modeling-and-simulation governance into a single implementation pathway. First, metropolitan rail agencies have been advised to prioritize station-focused constraint mitigation because station crowding and circulation pressure and dwell-time variability have been rated as the most severe interface constraints; therefore, agencies have been recommended to implement structured passenger-flow management protocols that have included peak-period gating or metering, directional circulation assignments, queue channelization at pinch points, platform marshaling during surges, and real-time dwell management rules that have balanced safety and service regularity. Second, operations and planning teams have been recommended to institutionalize scenario analysis as a routine decision practice by maintaining a standardized “scenario library” that has covered recurring interface conditions such as peak overload, special-event surges, junction conflicts, terminal turnback constraints, and disruption patterns, and by requiring that timetable revisions and major station-management decisions have been supported by scenario comparisons rather than single-point estimates. Third, because validation/verification rigor has been the lowest-rated modeling capability dimension and has been tied conceptually to safety and controllability outcomes, the study has recommended establishing a formal model governance program that has included documented assumptions, calibration and validation checklists, sensitivity testing standards, version control, and audit trails for model updates so that operational leaders have trusted model outputs when they have been used for high-stakes interventions. Fourth, decision integration has been recommended as a key implementation lever; therefore, agencies have been

advised to embed modeling outputs into established governance cycles by adding model-based indicators to weekly performance reviews, station readiness meetings, disruption debriefs, and timetable-change approvals, and by translating technical outputs into decision-ready formats such as “expected impact ranges,” “risk flags,” and “trigger thresholds” that have been understandable to non-modeling units. Fifth, corridor-level access friction and barrier effects have required coordinated action with municipal partners; thus, joint rail-city programs have been recommended to improve station-area permeability through safer crossings, improved pedestrian and cycling connections to stations, optimized feeder-bus access layouts, and precinct design adjustments that have reduced conflict between rail access flows and surrounding street networks. Sixth, environmental disturbance constraints have been recommended to be handled proactively through corridor exposure mapping, targeted mitigation at sensitive receivers, and operational-infrastructure coordination on speed profiles, track maintenance regimes, and buffering strategies that have balanced service goals with urban acceptability requirements. Finally, capability-building has been recommended through cross-functional training and staffing strategies that have connected modelers with station managers and control-room staff, ensuring that modeling has been used as a shared organizational capability rather than a siloed technical function; this has included the recommendation to define clear roles for data stewardship, modeling ownership, and operational sign-off so that the modeling pipeline has remained reliable, secure, and continuously usable for managing rail-urban interface constraints in the metropolitan system.

LIMITATIONS

This study has acknowledged several limitations that have influenced how the findings have been interpreted and how far the results have been generalized beyond the selected metropolitan case context. First, the research design has been cross-sectional, meaning that all measures have been captured at a single point in time and the statistical relationships identified through correlation and regression have not established temporal causality; therefore, although computational modeling and simulation capability and decision integration have predicted constraint-management effectiveness within the dataset, the direction of influence has not been confirmed definitively and reciprocal dynamics have remained plausible, such as stronger-performing organizations investing more in modeling practices. Second, the study has relied on self-reported Likert-scale perceptions rather than purely objective operational indicators, which has introduced the possibility of response bias, including social desirability, organizational defensiveness, role-based optimism, or differences in interpretation of scale anchors across departments; while reliability evidence has indicated strong internal consistency, perceptual measures have still reflected subjective judgments that may not have perfectly matched operational metrics such as headway variability, dwell distributions, delay minutes, or platform density. Third, the case-study boundary has limited external validity because rail-urban interface constraints and their governance have differed substantially across metropolitan regions due to differences in network topology, station design, signaling systems, land-use intensity, regulatory regimes, and institutional coordination structures; as a result, the magnitude of coefficients and the ranking of constraints observed in this case may not have transferred directly to cities with different ridership patterns, infrastructure typologies, or management cultures. Fourth, the sampling strategy has been purposive and functionally stratified, and although coverage across key roles has been achieved, the sample has still depended on access and willingness to participate, which has created potential nonresponse bias if highly burdened operations staff or senior decision makers have participated less frequently than other groups. Fifth, common-method effects have remained a potential concern because key predictors and outcomes have been measured using the same instrument and response context; screening tests have suggested that a single factor has not dominated variance, yet such diagnostics have not eliminated shared method inflation entirely, especially when constructs have been conceptually related. Sixth, the study has modeled complex rail-urban interface processes using aggregated construct scores, and this approach has simplified a reality that may have included nonlinear effects, threshold behaviors, and interaction patterns that have not been fully captured by linear regression, particularly under extreme peak loads or major disruptions. Finally, the construct set has focused on capability, integration, constraint severity, and effectiveness, and it has not exhaustively modeled other determinants such as budget cycles, labor constraints, political pressures, vendor

dependence, cyber/IT resilience issues, or detailed infrastructure condition variables, meaning that omitted factors may have contributed to unexplained variance even though model fit has been substantial. These limitations have not invalidated the study's conclusions within the case setting, but they have framed the results as empirically grounded associations that have required cautious generalization and have benefited from triangulation with longitudinal designs, multi-city replication, and integration of objective operational performance data in future extensions.

REFERENCES

- [1]. Abril, M., Barber, F., Ingolotti, L., Salido, M. A., Tormos, P., & Lova, A. (2008). An assessment of railway capacity. *Transportation Research Part E: Logistics and Transportation Review*, 44(5), 774-806. <https://doi.org/10.1016/j.tre.2007.04.001>
- [2]. Ahmadi, M., Eftekhari, M., & Nasiri, S. (2022). Train-induced vibrations: Effects, assessment, and mitigation in urban environments. *Sustainability*, 14, 53119. <https://doi.org/10.3390/su14053119>
- [3]. Baker, J. (2012). The Technology–Organization–Environment framework. In Y. K. Dwivedi, M. R. Wade, & S. L. Schneberger (Eds.), *Information systems theory: Explaining and predicting our digital society* (Vol. 1). Springer. https://doi.org/10.1007/978-1-4419-6108-2_12
- [4]. Berger, A., Gebhardt, A., Müller-Hannemann, M., & Ostrowski, M. (2011). *Stochastic delay prediction in large train networks* 11th Workshop on Algorithmic Approaches for Transportation Modelling, Optimization, and Systems (ATMOS 2011),
- [5]. Borgman, H. P., Bahli, B., Heier, H., & Schewski, F. (2013). *Cloudrise: Exploring cloud computing adoption and governance with the TOE framework* 2013 46th Hawaii International Conference on System Sciences,
- [6]. Caset, F., Vale, D. S., & Viana, C. M. (2018). Measuring the accessibility of railway stations in the Brussels Regional Express Network: A node-place modeling approach. *Networks and Spatial Economics*, 18(3), 495-530. <https://doi.org/10.1007/s11067-018-9409-y>
- [7]. Cavana, R. Y., Corbett, L. M., & Lo, Y. L. (2007). Developing zones of tolerance for managing passenger rail service quality. *International Journal of Quality & Reliability Management*, 24(1), 7-31. <https://doi.org/10.1108/02656710710720303>
- [8]. Chorus, P., & Bertolini, L. (2011). An application of the node-place model to explore the spatial development dynamics of station areas in Tokyo. *Journal of Transport and Land Use*, 4(1), 45-58. <https://doi.org/10.5198/jtlu.v4i1.145>
- [9]. Connolly, D. P., Marecki, G. P., Kouroussis, G., Thalassinakis, I., & Woodward, P. K. (2016). The growth of railway ground vibration problems – A review. *Science of the Total Environment*, 568, 1276-1282. <https://doi.org/10.1016/j.scitotenv.2015.09.101>
- [10]. Corman, F., D'Ariano, A., Pacciarelli, D., & Pranzo, M. (2010). Centralized versus distributed systems to reschedule trains in two dispatching areas. *Public Transport*, 2(3), 219-247. <https://doi.org/10.1007/s12469-010-0032-7>
- [11]. D'Acerno, L., Botte, M., Placido, A., Caropreso, C., & Montella, B. (2017). Methodology for determining dwell times consistent with passenger flows in the case of metro services. *Urban Rail Transit*, 3(2), 73-89. <https://doi.org/10.1007/s40864-017-0062-4>
- [12]. D'Ariano, A., Corman, F., Fujiyama, T., Meng, L., & Pellegrini, P. (2018). Simulation and optimization for railway operations management. *Journal of Advanced Transportation*, 2018, 4896748. <https://doi.org/10.1155/2018/4896748>
- [13]. Dewilde, T., Sels, P., Cattrysse, D., & Vansteenwegen, P. (2014). Improving the robustness in railway station areas. *European Journal of Operational Research*, 235(1), 276-286. <https://doi.org/10.1016/j.ejor.2013.10.062>
- [14]. Dröes, M. I., & Rietveld, P. (2015). Rail-based public transport and urban spatial structure: The interplay between network design, congestion and urban form. *Transportation Research Part B: Methodological*, 81, 421-439. <https://doi.org/10.1016/j.trb.2015.07.004>
- [15]. Dubroca-Voisin, M., Kabalan, B., & Leurent, F. (2019). On pedestrian traffic management in railway stations: Simulation needs and model assessment. *Transportation Research Procedia*, 37, 3-10. <https://doi.org/10.1016/j.trpro.2018.12.159>
- [16]. Ewing, R., & Cervero, R. (2010). Travel and the built environment: A meta-analysis. *Journal of the American Planning Association*, 76(3), 265-294. <https://doi.org/10.1080/01944361003766766>
- [17]. Fu, Y., Sun, H., Kang, L., & Wu, J. (2020). Passenger flow control strategies for urban rail transit networks. *Applied Mathematical Modelling*, 82, 168-188. <https://doi.org/10.1016/j.apm.2020.01.041>
- [18]. Gao, S., Yang, L., Gao, Z., & Xu, X. (2014). An integrated control model for headway regulation and energy saving in urban rail transit. *IEEE Transactions on Intelligent Transportation Systems*. <https://doi.org/10.1109/tits.2014.2366495>
- [19]. Goverde, R. M. P. (2007). Railway timetable stability analysis using max-plus system theory. *Transportation Research Part B: Methodological*, 41(2), 179-201. <https://doi.org/10.1016/j.trb.2006.02.003>
- [20]. Habibullah, S. M., & Muhammad Mohiul, I. (2023). Digital Twin-Driven Thermodynamic and Fluid Dynamic Simulation For Exergy Efficiency In Industrial Power Systems. *American Journal of Scholarly Research and Innovation*, 2(01), 224–253. <https://doi.org/10.63125/k135kt69>
- [21]. Hair, J. F., Ringle, C. M., & Sarstedt, M. (2011). PLS-SEM: Indeed a silver bullet. *Journal of Marketing Theory and Practice*, 19(2), 139-152. <https://doi.org/10.2753/mtp1069-6679190202>
- [22]. Harrod, S., Cerreto, F., & Nielsen, O. A. (2019). A closed form railway line delay propagation model. *Transportation Research Part C: Emerging Technologies*, 102, 189-209. <https://doi.org/10.1016/j.trc.2019.02.022>

- [23]. Hassannayebi, E., Sajedinejad, A., & Mardani, S. (2014). Urban rail transit planning using a two-stage simulation-based optimization approach. *Simulation Modelling Practice and Theory*, 49, 151-166.
<https://doi.org/10.1016/j.simpat.2014.09.004>
- [24]. Javed Hasan, T., & Waladur, R. (2023). AI-Driven Cybersecurity, IOT Networking, And Resilience Strategies For Industrial Control Systems: A Systematic Review For U.S. Critical Infrastructure Protection. *International Journal of Scientific Interdisciplinary Research*, 4(4), 144–176. <https://doi.org/10.63125/mbyhj941>
- [25]. Jinnat, A., & Md. Kamrul, K. (2021). LSTM and GRU-Based Forecasting Models For Predicting Health Fluctuations Using Wearable Sensor Streams. *American Journal of Interdisciplinary Studies*, 2(02), 32-66.
<https://doi.org/10.63125/1p8gbp15>
- [26]. Kersbergen, B., van den Boom, T., & De Schutter, B. (2016). Distributed model predictive control for railway traffic management. *Transportation Research Part C: Emerging Technologies*, 68, 462-489.
<https://doi.org/10.1016/j.trc.2016.05.006>
- [27]. Kutub Uddin, A., Md Mostafizur, R., Afrin Binta, H., & Maniruzzaman, B. (2022). Forecasting Future Investment Value with Machine Learning, Neural Networks, And Ensemble Learning: A Meta-Analytic Study. *Review of Applied Science and Technology*, 1(02), 01-25. <https://doi.org/10.63125/edxgig56>
- [28]. Li, Y., Yang, X., Wu, J., Sun, H., Guo, X., & Zhou, L. (2021). Discrete-event simulations for metro train operation under emergencies: A multi-agent based model with parallel computing. *Physica A: Statistical Mechanics and its Applications*, 585, 125964. <https://doi.org/10.1016/j.physa.2021.125964>
- [29]. Liang, C., Ghazel, M., Cazier, O., & El-Koursi, E.-M. (2017). Risk analysis on level crossings using a causal Bayesian network based approach. *Transportation Research Procedia*, 25, 2167-2181.
<https://doi.org/10.1016/j.trpro.2017.05.418>
- [30]. Lyu, G., Bertolini, L., & Pfeffer, K. (2016). Developing a TOD typology for Beijing metro station areas. *Journal of Transport Geography*, 55, 40-50. <https://doi.org/10.1016/j.jtrangeo.2016.07.002>
- [31]. Masud, R., & Md Sarwar Hossain, S. (2024). The Impact of Smart Materials And Fire-Resistant Structures On Safety In U.S. Public Infrastructure. *Journal of Sustainable Development and Policy*, 3(03), 44-86.
<https://doi.org/10.63125/ygr1yk30>
- [32]. Md, K., & Sai Praveen, K. (2024). Hybrid Discrete-Event And Agent-Based Simulation Framework (H-DEABSF) For Dynamic Process Control In Smart Factories. *ASRC Procedia: Global Perspectives in Science and Scholarship*, 4(1), 72–96.
<https://doi.org/10.63125/wcqq7x08>
- [33]. Md Nahid, H., & Tahmina Akter Bhuya, M. (2024). An Empirical Study of Big Data-Enabled Predictive Analytics And Their Impact On Financial Forecasting And Market Decision-Making. *Review of Applied Science and Technology*, 3(01), 143–182. <https://doi.org/10.63125/1mjfqf10>
- [34]. Md. Akbar, H. (2024). Computational Psychometrics and Digital Biomarker Modeling For Precision Mental Health Diagnostics. *International Journal of Scientific Interdisciplinary Research*, 5(2), 487–525.
<https://doi.org/10.63125/vg522x27>
- [35]. Md. Akbar, H., & Sharmin, A. (2022). Neurobiotechnology-Driven Regenerative Therapy Frameworks For Post-Traumatic Neural Recovery. *American Journal of Scholarly Research and Innovation*, 1(02), 134–170.
<https://doi.org/10.63125/24s6kt66>
- [36]. Md. Foysal, H., & Abdulla, M. (2024). Agile And Sustainable Supply Chain Management Through AI-Based Predictive Analytics And Digital Twin Simulation. *International Journal of Scientific Interdisciplinary Research*, 5(2), 343–376. <https://doi.org/10.63125/sejyk977>
- [37]. Md. Foysal, H., & Subrato, S. (2022). Data-Driven Process Optimization in Automotive Manufacturing A Machine Learning Approach To Waste Reduction And Quality Improvement. *Journal of Sustainable Development and Policy*, 1(02), 87-133. <https://doi.org/10.63125/2hk0qd38>
- [38]. Md. Jobayer Ibne, S., & Aditya, D. (2024). Machine Learning and Secure Data Pipeline Frameworks For Improving Patient Safety Within U.S. Electronic Health Record Systems. *American Journal of Interdisciplinary Studies*, 5(03), 43–85. <https://doi.org/10.63125/nb2c1f86>
- [39]. Md. Mosheur, R., & Md Arman, H. (2024). Impact Of Big Data and Predictive Analytics On Financial Forecasting Accuracy And Decision-Making In Global Capital Markets. *American Journal of Scholarly Research and Innovation*, 3(02), 99–140. <https://doi.org/10.63125/hg37h121>
- [40]. Md. Rabiul, K., & Khairul Alam, T. (2024). Impact Of IOT and Blockchain Integration On Real-Time Supply Chain Transparency. *International Journal of Scientific Interdisciplinary Research*, 5(2), 449–486.
<https://doi.org/10.63125/2yc6e230>
- [41]. Md. Rabiul, K., & Mohammad Mushfequr, R. (2023). A Quantitative Study On Erp-Integrated Decision Support Systems In Healthcare Logistics. *Review of Applied Science and Technology*, 2(01), 142–184.
<https://doi.org/10.63125/c92bbj37>
- [42]. Md. Rabiul, K., & Samia, A. (2021). Integration Of Machine Learning Models And Advanced Computing For Reducing Logistics Delays In Pharmaceutical Distribution. *American Journal of Advanced Technology and Engineering Solutions*, 1(4), 01-42. <https://doi.org/10.63125/ahnkqj11>
- [43]. Mikalef, P., Krogstie, J., Pappas, I. O., & Pavlou, P. A. (2020). Exploring the relationship between big data analytics capability and competitive performance: The mediating roles of dynamic and operational capabilities. *Information & Management*, 57(2), 103169. <https://doi.org/10.1016/j.im.2019.05.004>
- [44]. Mst. Shahrin, S., & Samia, A. (2023). High-Performance Computing For Scaling Large-Scale Language And Data Models In Enterprise Applications. *ASRC Procedia: Global Perspectives in Science and Scholarship*, 3(1), 94–131.
<https://doi.org/10.63125/e7yfwm87>

- [45]. Muhammad Mohiul, I. (2020). Impact Of Digital Construction Management Platforms on Project Performance Post-Covid-19. *American Journal of Interdisciplinary Studies*, 1(04), 01-25. <https://doi.org/10.63125/nqp0zh08>
- [46]. Muhammad Mohiul, I., & Rahman, M. D. H. (2021). Quantum-Enhanced Charge Transport Modeling In Perovskite Solar Cells Using Non-Equilibrium Green's Function (NEGF) Framework. *Review of Applied Science and Technology*, 6(1), 230–262. <https://doi.org/10.63125/tdbjaj79>
- [47]. Norman, G. (2010). Likert scales, levels of measurement and the “laws” of statistics. *Advances in Health Sciences Education*, 15, 625–632. <https://doi.org/10.1007/s10459-010-9222-y>
- [48]. Oliveira, T., & Martins, M. F. (2010). Understanding e-business adoption across industries in European countries. *Industrial Management & Data Systems*, 110(9), 1337-1354. <https://doi.org/10.1108/02635571011087428>
- [49]. Papa, E., & Bertolini, L. (2015). Accessibility and transit-oriented development in European metropolitan areas. *Journal of Transport Geography*, 47, 70-83. <https://doi.org/10.1016/j.jtrangeo.2015.07.003>
- [50]. Pefitsi, S., Jenelius, E., & Cats, O. (2022). Modeling the effect of real-time crowding information (RTCI) on passenger distribution in trains. *Transportation Research Part A: Policy and Practice*, 167, 103586. <https://doi.org/10.1016/j.tra.2022.10.011>
- [51]. Rahman, M. D. H. (2022). Modelling The Impact Of Temperature Coefficients On PV System Performance In Hot And Humid Climates. *International Journal of Scientific Interdisciplinary Research*, 1(01), 194–237. <https://doi.org/10.63125/abj6wy92>
- [52]. Rahman, S. M. T., & Abdul, H. (2021). The Role Of Predictive Analytics In Enhancing Agribusiness Supply Chains. *Review of Applied Science and Technology*, 6(1), 183–229. <https://doi.org/10.63125/n9z10h68>
- [53]. Rakibul, H., & Khairul Alam, T. (2023). A Systematic Review of Predictive Analytics In Marketing Decision-Making Exploring AI-Driven Consumer Segmentation And AB Testing. *International Journal of Business and Economics Insights*, 3(1), 68–96. <https://doi.org/10.63125/2hvf110>
- [54]. Reusser, D. E., Loukopoulos, P., Staufacher, M., & Scholz, R. W. (2008). Classifying railway stations for sustainable transitions – Balancing node and place functions. *Journal of Transport Geography*, 16(3), 191-202. <https://doi.org/10.1016/j.jtrangeo.2007.05.004>
- [55]. Rifat, C., & Rebeka, S. (2023). The Role Of ERP-Integrated Decision Support Systems In Enhancing Efficiency And Coordination In Healthcare Logistics: A Quantitative Study. *International Journal of Scientific Interdisciplinary Research*, 4(4), 265–285. <https://doi.org/10.63125/c7srk144>
- [56]. Saba, A., & Md. Sakib Hasan, H. (2024). Machine Learning And Secure Data Pipelines For Enhancing Patient Safety In Electronic Health Record (EHR) Among U.S. Healthcare Providers. *ASRC Procedia: Global Perspectives in Science and Scholarship*, 4(1), 124–168. <https://doi.org/10.63125/qm4he747>
- [57]. Sabuj Kumar, S. (2023). Integrating Industrial Engineering and Petroleum Systems With Linear Programming Model For Fuel Efficiency And Downtime Reduction. *Journal of Sustainable Development and Policy*, 2(04), 108-139. <https://doi.org/10.63125/v7d6a941>
- [58]. Sabuj Kumar, S. (2024). Petroleum Storage Tank Design and Inspection Using Finite Element Analysis Model For Ensuring Safety Reliability And Sustainability. *Review of Applied Science and Technology*, 3(04), 94–127. <https://doi.org/10.63125/a18zw719>
- [59]. Sai Praveen, K. (2024). AI-Enhanced Data Science Approaches For Optimizing User Engagement In U.S. Digital Marketing Campaigns. *Journal of Sustainable Development and Policy*, 3(03), 01-43. <https://doi.org/10.63125/65ebsn47>
- [60]. Saikat, S., & Aditya, D. (2023). Reliability-Centered Maintenance Optimization Using Multi-Objective Ai Algorithms In Refinery Equipment. *American Journal of Scholarly Research and Innovation*, 2(01), 389–411. <https://doi.org/10.63125/6a6kqm73>
- [61]. Saw, Y. Q., Dissanayake, D., Ali, F., & Bentotage, T. (2020). Passenger satisfaction towards metro infrastructures, facilities and services. *Transportation Research Procedia*, 48, 3980-3995. <https://doi.org/10.1016/j.trpro.2020.08.290>
- [62]. Shaikat, B., & Aditya, D. (2024). Graph Neural Network Models For Predicting Cyber Attack Patterns In Critical Infrastructure Systems. *Review of Applied Science and Technology*, 3(01), 68–105. <https://doi.org/10.63125/pmnqk63>
- [63]. Shen, W., Xiao, W., & Wang, X. (2016). Passenger satisfaction evaluation model for urban rail transit: A structural equation modeling based on partial least squares. *Transport Policy*, 46, 20-31. <https://doi.org/10.1016/j.tranpol.2015.10.006>
- [64]. Shi, J., Yang, L., Yang, J., & Gao, Z. (2018). Service-oriented train timetabling with collaborative passenger flow control on an oversaturated metro line: An integer linear optimization approach. *Transportation Research Part B: Methodological*, 110, 26-59. <https://doi.org/10.1016/j.trb.2018.02.003>
- [65]. Tavakol, M., & Dennick, R. (2011). Making sense of Cronbach's alpha. *International Journal of Medical Education*, 2, 53-55. <https://doi.org/10.5116/ijme.4dfb.8dfd>
- [66]. Tirachini, A., Sun, L., Erath, A., & Chakirov, A. (2016). Valuation of sitting and standing in metro trains using revealed preferences. *Transport Policy*, 47, 94-104. <https://doi.org/10.1016/j.tranpol.2015.12.004>
- [67]. Torija, A. J., Ruiz, D. P., De Coensel, B., Botteldooren, D., Berglund, B., & Ramos-Ridao, Á. (2011). Relationship between road and railway noise annoyance and overall indoor sound exposure. *Transportation Research Part D: Transport and Environment*, 16(1), 15-22. <https://doi.org/10.1016/j.trd.2010.07.012>
- [68]. Tortainchai, N., Wong, H., Winslett, D., & Fujiyama, T. (2021). Train dwell time efficiency evaluation with data envelopment analysis: Case study of London Underground Victoria Line. *Transportation Research Record*, 2676(3), 728-739. <https://doi.org/10.1177/03611981211056640>

- [69]. Vale, D. S. (2015). Transit-oriented development, integration of land use and transport, and pedestrian accessibility: Combining node-place model with pedestrian shed ratio to evaluate and classify station areas in Lisbon. *Journal of Transport Geography*, 45, 70-80. <https://doi.org/10.1016/j.jtrangeo.2015.04.009>
- [70]. van Eldijk, J. (2019). The wrong side of the tracks: Quantifying barrier effects of transport infrastructure on local accessibility. *Transportation Research Procedia*, 41, 368-380. <https://doi.org/10.1016/j.trpro.2019.12.005>
- [71]. Wang, C. L., & Ahmed, P. K. (2007). Dynamic capabilities: A review and research agenda. *International Journal of Management Reviews*, 9(1), 31-51. <https://doi.org/10.1111/j.1468-2370.2007.00201.x>
- [72]. Yalçınkaya, Ö., & Bayhan, G. M. (2009). Modelling and optimization of average travel time for a metro line by simulation and response surface methodology. *European Journal of Operational Research*, 196(1), 225-233. <https://doi.org/10.1016/j.ejor.2008.03.010>
- [73]. Yang, J., Zhu, S., Zhai, W., Kouroussis, G., Wang, X., & Xu, L. (2019). Prediction and mitigation of train-induced vibrations of large-scale building constructed on subway tunnel. *Science of the Total Environment*, 668, 485-499. <https://doi.org/10.1016/j.scitotenv.2019.02.397>
- [74]. Yuan, J., & Hansen, I. A. (2007). Optimizing capacity utilization of stations by estimating knock-on train delays. *Transportation Research Part B: Methodological*, 41(2), 202-217. <https://doi.org/10.1016/j.trb.2006.02.004>
- [75]. Zamal Haider, S., & Mst. Shahrin, S. (2021). Impact Of High-Performance Computing In The Development Of Resilient Cyber Defense Architectures. *American Journal of Scholarly Research and Innovation*, 1(01), 93-125. <https://doi.org/10.63125/fradxg14>
- [76]. Zhou, J., Wu, Y., Mao, X., Guo, S., & Zhang, M. (2019). Congestion evaluation of pedestrians in metro stations based on normal-cloud theory. *Applied Sciences*, 9(17), 3624. <https://doi.org/10.3390/app9173624>
- [77]. Zhu, K., Kraemer, K. L., & Xu, S. (2006). The process of innovation assimilation by firms in different countries: A technology diffusion perspective on e-business. *Management Science*, 52(10), 1557-1576. <https://doi.org/10.1287/mnsc.1050.0487>
- [78]. Zou, C., Ng, C. F., & Liu, Y. (2020). Train-induced building vibration and radiated noise: A field investigation in a university campus. *Sustainability*, 12(3), 937. <https://doi.org/10.3390/su12030937>
- [79]. Zulqarnain, F. N. U. (2022). Policy Optimization for Sustainable Energy Security: Data-Driven Comparative Analysis Between The U.S. And South Asia. *American Journal of Interdisciplinary Studies*, 3(04), 294-331. <https://doi.org/10.63125/v4e4m413>
- [80]. Zulqarnain, F. N. U., & Subrato, S. (2021). Modeling Clean-Energy Governance Through Data-Intensive Computing And Smart Forecasting Systems. *International Journal of Scientific Interdisciplinary Research*, 2(2), 128-167. <https://doi.org/10.63125/wnd6qs51>
- [81]. Zulqarnain, F. N. U., & Subrato, S. (2023). Intelligent Climate Risk Modeling For Robust Energy Resilience And National Security. *Journal of Sustainable Development and Policy*, 2(04), 218-256. <https://doi.org/10.63125/jmer2r39>